

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY  
Log No. 116253  
Permit No. 31222/51638  
Basin 106

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 68339 ✓

1 OWNER Douglas county Public Works  
MAILING ADDRESS 1120 Airport Road, Building F2  
Minden, NV. 89423

ADDRESS AT WELL LOCATION Approx. 200' south of the corner  
of Raeline and Clapham Lane in North Valley 1391 Raeline Ln.  
Subdivision Name: \_\_\_\_\_ County: Douglas

2 LOCATION NE 1/4 NE 1/4 Sec 33 T1438N N3R 20 E  
PERMIT/WAIVER No. 51638/31222 1490-33-501-013  
Issued by Water Resources Parcel No. \_\_\_\_\_

Latitude 39 02.310N UTM E  NAD 27  
Longitude 119 44.009W N  NAD 83/WGS 84

3 TYPE OF WELL  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

Is this well being plugged because a replacement well was drilled? \_\_\_\_\_  
If yes, what is replacement well NO? \_\_\_\_\_

Is there an existing well log? yes  
If yes, what is NDWR well log #? 18123

4 EXISTING WELL CONSTRUCTION  
Depth Drilled 220 Feet Depth Cased 220 Feet

7 WELL PLUGGING PROCEDURE  
Was well cleaned out to total depth?  yes  no

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
12	n/a	.250	1	220

If well was not cleaned out to total depth, please explain why: \_\_\_\_\_  
Was the well contaminated?  yes  no  
Was the casing pulled?  yes  no  
Was the casing over drilled?  yes  no

Existing Perforations:

Type of perforation	Size of perforation	factory mill slot
From	n/a	feet to n/a feet
From		feet to  feet
From		feet to  feet
From		feet to  feet
From		feet to  feet

Additional Perforations:

Type of perforator used:	Mills Knife
From <u>60</u> feet to <u>0</u> feet	Number of perfs per linear foot <u>6</u>
From  feet to  feet	Number of perfs per linear foot
From  feet to  feet	Number of perfs per linear foot
From  feet to  feet	Number of perfs per linear foot
From  feet to  feet	Number of perfs per linear foot
From  feet to  feet	Number of perfs per linear foot

5 WATER LEVEL  
Static water level 34.9 feet below land surface  
Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

8 WELL PLUGGING MATERIALS  
Material Used  
From 220 feet to 0 feet  Pumped  Poured  
From  feet to  feet  Pumped  Poured

6 Additional Notes or Comments

Removed 147' of 3" drop pipe with 25hp pump. Measured static water level at 34.9' and depth of well at 212'. Bailed debris from well to a depth of 218' where we seemed to hit a hard bottom. We then installed 12" mills knife and cut 6 rows per foot from 60' back to surfac. We installed 2" tremmie pipe to 210'. We had neat cement delivered the folowing day and pumped in 8 yards of neat cement. The casing was cut off 2' bgs.

Neat Cement Fluid Weight 14.4 lbs/gal  
Bentonite Grout \_\_\_\_\_ % bentonite  
Date Started 10/7/2012  
Date Completed 10/08/2012

NAD 27  
39.038591°N  
119.732472°W

9 DRILLER'S CERTIFICATION  
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
Name Carson Pump, LLC Contractor  
Address P.O. Box 20159 Contractor  
Carson City, NV. 89721  
Nevada contractor's license number issued by the State Contractor's Board 39920  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2265  
Signed [Signature]  
By driller performing actual drilling on site or contractor  
Date 10/31/2012