

Well name:  
WS-3

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S REPORT

OFFICE USE ONLY  
Log No. 116316  
Permit No. 81080T  
Basin 072

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 66304

1. OWNER Florida Canyon Mining  
MAILING ADDRESS P.O. Box 330  
Imlay, NV 89418

ADDRESS AT WELL LOCATION Standard Mine Imlay, NV

Subdivision Name: \_\_\_\_\_ County: Pershing

2. LOCATION SE 1/4 NW 1/4 Sec 35 T 31N N/S R 33 E Latitude W118°14.331 UTM E  NAD 27  
PERMIT/WAIVER No. 81080T Longitude N40°30.515 N  NAD 83/WGS 84

Issued by Water Resources Parcel No. \_\_\_\_\_

3. WORKED PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Other

4. PROPOSED USE  
 Domestic Mining/Milling  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other

6. LITHOLOGIC LOG

| Material                         | Water Strata | From | To  | Thick-ness |
|----------------------------------|--------------|------|-----|------------|
| fill sand & gravel               |              | 0    | 10  | 10         |
| gravel some clay                 |              | 10   | 30  | 20         |
| silt stone & grave & boulders    |              | 30   | 160 | 130        |
| limestone float & silt stone mix | 250          | 160  | 260 | 100        |
| broken lime stone                | 260          | 260  | 400 | 140        |
|                                  | to           |      |     |            |
|                                  | 400          |      |     |            |

9. WELL CONSTRUCTION

Depth Drilled 400 Feet Depth Cased 362 Feet

HOLE DIAMETER (BIT SIZE)

|        | From | To  |
|--------|------|-----|
| 26     | 0    | 20  |
| 17 1/2 | 20   | 400 |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|--------------------|---------------------|-------------------------|-------------|-----------|
| 20                 |                     | 3.50                    | 0           | 20        |
| 12                 |                     | 2.50                    | +1 1/2      | 362       |

Perforations:

Type of perforation mill slot  
Size of perforation 125 x 2 1/2 slot

| From | feet to | feet |
|------|---------|------|
| 242  | 362     |      |
|      |         |      |
|      |         |      |
|      |         |      |
|      |         |      |

Annular Seal:  Yes  No

Neat Cement 0 to 50  Pumped  Poured  
 Cement Grout to  Pumped  Poured  
 Concrete Grout to  Pumped  Poured  
 ≥30% Bentonite Grout to  Pumped  Poured

Gravel Pack:  Yes  No 50 to 362  Pumped  Poured  
Type: pea gravel

Bentonite Chips:  Yes  No to  Pumped  Poured  
Type: \_\_\_\_\_

Date started: 16-Nov 20 11  
Date completed: 16-Dec 20 11

7. Water Level  
Static water level: 185 feet below land surface  
Artesian Flow: \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water Temperature: cold °F  
Quality: \_\_\_\_\_

8. WELL TEST DATA

TEST METHOD:  Bailer  Pump  Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|--------|-------------------------------|--------------|
| 100+   |                               | 12           |
|        |                               |              |
|        |                               |              |
|        |                               |              |

10. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Alternative Drilling  
Contractor

Address P.O. Box 281166  
Contractor

Lamoille, NV 89828

Nevada contractor's license number issued by the State Contractor's Board 73955

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1689

Signed [Signature]  
By driller performing actual drilling on site or contractor

Date 1-18-2012

RECEIVED  
2012 JAN 20 AM 11:28  
STATE ENGINEERS OFFICE

40. 508677°N  
118. 237871°W NAD27

USE ADDITIONAL SHEETS IF NECESSARY

(Rev. 06-08)