

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
**WELL DRILLER'S PLUGGING REPORT**

OFFICE USE ONLY  
Log No. 116 351  
Permit No. 65 781  
Basin 137B

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 69255

1. OWNER Round Mountain Gold Corp. "DW-25" ADDRESS AT WELL LOCATION Round Mtn Gold Mine, Round Mtn., NV.  
MAILING ADDRESS P.O. Box 480  
Round Mountain, NV. 89045 Subdivision Name: \_\_\_\_\_ County: Nye

2. LOCATION NE 1/4 SE 1/4 Sec 24 T10N R43E Latitude \_\_\_\_\_ UTM E 491965  NAD 27  
PERMIT/WAIVER NO. 65178T Longitude \_\_\_\_\_ N 4284138  NAD 83/WGS 84  
*Issued by Water Resources* Parcel No. \_\_\_\_\_

3. TYPE OF WELL  Domestic  Irrigation  Test  Municipal/Industrial  Monitor  Stock  
Is this well being plugged because a replacement well was drilled?  Yes  No  
If yes, what is replacement well NOI? \_\_\_\_\_  
Is there an existing well log?  Yes  No  
If yes, what is NDWR well log #? 78526

4. EXISTING WELL CONSTRUCTION  
Depth Drilled 1206 Feet Depth Cased 1200 Feet

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
12.75	33.6	.250	0	830

Existing Perforations:  
Type of perforation Johnson Wire Wrap  
Size of perforation .080  
From 158 feet to 458 feet  
From 640 feet to 800 feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

5. WATER LEVEL  
Static water level: 287 feet below land surface  
Artesian flow: N/A G.P.M. N/A P.S.I.  
Water Temperature: N/A °F Quality N/A

6. Additional Notes or Comments  
Well had been mined off 370'.  
  
540 cu. ft. Bentonite Grout  
112 cu. ft. Hole Plug  
103 cu. ft. Neat Cement

7. WELL PLUGGING PROCEDURE

Was well cleaned out to total depth?  Yes  No  
If well was not cleaned out to total depth, please explain why: \_\_\_\_\_

Was the well contaminated?  Yes  No  
Was the casing pulled?  Yes  No  
Was the casing over drilled?  Yes  No

If casing was left in place, please show where additional perforations were made:  
Additional Perforations:

Type of perforator used: Holt  
From 458 feet to 640 feet Number of perfs per linear foot 24  
From 0 feet to 158 feet Number of perfs per linear foot 24  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet Number of perfs per linear foot \_\_\_\_\_

8. WELL PLUGGING MATERIALS

Material Used			
From <u>150</u> feet to <u>830</u> feet	<u>Benton.</u>	<input checked="" type="checkbox"/> Pumped	<input type="checkbox"/> Poured
From <u>100</u> feet to <u>150</u> feet	<u>Hole P.</u>	<input type="checkbox"/> Pumped	<input checked="" type="checkbox"/> Poured
From <u>0</u> feet to <u>100</u> feet	<u>Neat C.</u>	<input type="checkbox"/> Pumped	<input checked="" type="checkbox"/> Poured
From _____ feet to _____ feet	_____	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
From _____ feet to _____ feet	_____	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
From _____ feet to _____ feet	_____	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured

Neat Cement Fluid Weight 15.6 lbs/gal  
Bentonite Grout 20 % bentonite

Date Started December 8, 2012  
Date Completed December 15, 2012

9. DRILLER'S CERTIFICATION

This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.

Name Boart Longyear (CONTRACTOR)

Address 2745 California Ave. (CONTRACTOR)

SLC., UT. 84104  
Nevada contractor's license number issued by the State Contractor's Board 0021976

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2462

Signed \_\_\_\_\_  
By driller performing actual drilling on site or contractor  
Date December 18, 2012

RECEIVED  
2012 DEC 24 PM 12:31  
STATE ENGINEERS OFFICE

38.707706° N  
117.092410° W NAD 27

(Rev 05-06)

USE ADDITIONAL SHEETS IF NECESSARY