STATE OF NEVADA

DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 116338
Permit No.
Basin 137B

PRINT OR TYPE ONLY

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 69245

1. OWNER Round Mountain Gold Corp. HD-12-FV1-F (well ID;)
MAILING ADDRESS P.O. Box 480
Round Mountain, NV. 89045

ADDRESS AT WELL LOCATION Round Mtn. Gold Mine
Round Mountain, NV
Subdivision Name: County: Nye

2. LOCATION NW¼NW¼ Sec29T10N/ R44E
PERMIT/WAIVER NO. M/O-1863 Parcel. No.
Issued by Water Resources

Latitude
Longitude

UTM E 493819 ☒ NAD 27
N 4283310 ☐ NAD 83/WGS 84

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other Horizontal Drain

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Tuff and Granite Lithics		0	520	520
Granite		520	620	100
Older Volcanics/Lithic Rich Tuff		620	740	120
Granite		740	1200	460

RECEIVED 2012 DEC 14 AM 11:14 STATE ENGINEERS OFFICE

2-5-13 Corrected as approved by D. Kohlman of Boart Longyear

Date started: November 21, 20 2012
Date completed: November 24, 20 2012

9. WELL CONSTRUCTION
Depth Drilled 1200 Feet Depth Cased 1195 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
7 Inches	0 Feet	15 Feet
5.75 Inches	15 Feet	1200 Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6.625	12.95	.188	15	+5
1.5	.69	.145	~~15~~ 1195	~~+5~~ 15

Perforations:
Type of perforation Slotted
Size of perforation .020
From 15 feet to 1195 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☒ Neat Cement 0 to 15 ☒ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured
Gravel Pack: ☐ Yes ☒ No to ☐ Pumped ☐ Poured
Type:
Bentonite Chips: ☐ Yes ☒ No to ☐ Pumped ☐ Poured
Type:

7. Water Level
Static water level: 390 feet below land surface
Artesian Flow: N/A G.P.M. N/A P.S.I
Water Temperature: N/A °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
5		.5

38.700259 °N NAD27
117.071080 °W

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Boart Longyear (CONTRACTOR)
Address 2745 California Ave. (CONTRACTOR)
SLC., UT. 84104
Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2329
Signed
By driller performing actual drilling on site or contractor
Date December 10, 2012

(Rev 05-06) USE ADDITIONAL SHEETS IF NECESSARY

Forms Provided by Forms-On-A-Disk · (214) 340-9429 · FormsOnADisk.com