

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
**WELL DRILLER'S PLUGGING REPORT**

OFFICE USE ONLY  
Log No. 116366  
Permit No. 56176T  
Basin 044

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 67590

1 OWNER YUKON-NEVADA GOLD CORP. ADDRESS AT WELL LOCATION JERRITT CANYON MILL SITE TAILINGS  
MAILING ADDRESS HC 31 BOX 78 POND DPS-3A  
ELKO, NV 89801 Subdivision Name: TRACK OF LAND County: ELKO

2 LOCATION NE 1/4 NW 1/4 Sec 4 T 40N N/S R 54 E Latitude 41.395701874 UTM E  NAD 27  
PERMIT/WAIVER No. 56176T Longitude 115.900491169 N  NAD 83/WGS 84  
Issued by Water Resources Parcel No.

3 TYPE OF WELL  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
Is this well being plugged because a replacement well was drilled? NO  
Is there an existing well log? YES  
If yes, what is replacement well NOI? If yes, what is NDWR well log #? 71647

4 EXISTING WELL CONSTRUCTION  
Depth Drilled 100 Feet Depth Cased 100 Feet

7 WELL PLUGGING PROCEDURE  
Was well cleaned out to total depth?  yes  no  
If well was not cleaned out to total depth, please explain why:

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6.625	PVC	SCH 80	+1	100

Was the well contaminated?  yes  no  
Was the casing pulled?  yes  no  
Was the casing over drilled?  yes  no  
If casing was left in place, please show where additional perforations were made:  
Additional Perforations:

Existing Perforations:

Type of perforation	Size of perforation	From	feet to	To	feet
SLOT	0.02	80	feet to	100	feet
			feet to		feet
			feet to		feet
			feet to		feet
			feet to		feet

Type of perforator used: HOLTZ AIR PERFORATOR

From	feet to	feet	Number of perfs per linear foot
30	feet to	80	20
	feet to		

5 WATER LEVEL  
Static water level 95 feet below land surface  
Artesian flow  G.P.M.  P.S.I.  
Water temperature   °F Quality  

8 WELL PLUGGING MATERIALS

From	feet to	feet	Material Used	<input checked="" type="checkbox"/> Pumped	<input type="checkbox"/> Poured
20	feet to	100	SUPER PLUG	<input checked="" type="checkbox"/>	<input type="checkbox"/>
0	feet to	20		<input type="checkbox"/>	<input checked="" type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>

6 Additional Notes or Comments  
TRIED TO PULL CASING AND IT DIDN'T MOVE  
STATE ENGINEER  
2011 SEP 30 AM 11:47

Neat Cement Fluid Weight 15 lbs/gal  
Bentonite Grout 20 % bentonite  
Date Started 16-Sep-11  
Date Completed 16-Sep-11

9 DRILLER'S CERTIFICATION  
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
Name HACKWORTH DRILLING INC Contractor  
Address P. O. BOX 850 Contractor  
ELKO, NV 89803  
Nevada contractor's license number issued by the State Contractor's Board 020582  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1408-T1  
Signed Antonia Elmer  
By driller performing actual drilling on site or contractor  
Date 20-Sep-11

(Rev. 05-06) USE ADDITIONAL SHEETS IF NECESSARY  
RECEIVED  
41.395793°N NAD27  
115.899576°W