

**ORIGINAL**

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
**WELL DRILLER'S PLUGGING REPORT**

OFFICE USE ONLY	
Log No.	116368
Permit No.	60423
Basin	070

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 67741 ✓

1 OWNER DIAMOND PLASTICS  
MAILING ADDRESS PO BOX 189 GOLCONDA, NV 89414

ADDRESS AT WELL LOCATION DIAMOND PLASTICS

Subdivision Name: \_\_\_\_\_ County: Humboldt

2 LOCATION NE ¼ NE ¼ Sec 29 T 36N N/S R 40 E  
PERMIT/WAIVER No. 60423  
Issued by Water Resources Parcel No.

Latitude 40° 58' 24" N UTM E  NAD 27  
Longitude 117° 29' 27" W N  NAD 83/WGS 84

3 TYPE OF WELL  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

Is this well being plugged because a replacement well was drilled? NO  
If yes, what is replacement well NOI? \_\_\_\_\_

Is there an existing well log? YES  
If yes, what is NDWR well log #? 50014

4 EXISTING WELL CONSTRUCTION  
Depth Drilled 210 Feet Depth Cased 200 Feet

7 WELL PLUGGING PROCEDURE  
Was well cleaned out to total depth?  yes  no

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8 5/8"		.188"	+1'	200'

If well was not cleaned out to total depth, please explain why: \_\_\_\_\_

Existing Perforations:

Type of perforation	Size of perforation	From	feet to	To	feet
MILL SLOT	.125"	120'	feet to	200'	feet
			feet to		feet
			feet to		feet
			feet to		feet
			feet to		feet

Was the well contaminated?  yes  no  
Was the casing pulled?  yes  no  
Was the casing over drilled?  yes  no

If casing was left in place, please show where additional perforations were made:

Additional Perforations:

Type of perforator used:	From	feet to	feet	Number of perms per linear foot
MILLS KNIFE	100'	feet to	120'	4 Rows
		feet to		

5 WATER LEVEL  
Static water level 15' feet below land surface  
Artesian flow NO G.P.M. 0 P.S.I.  
Water temperature COOL °F Quality \_\_\_\_\_

8 WELL PLUGGING MATERIALS

6 Additional Notes or Comments

Plugging well log # 50014

From	feet to	feet	Material Used	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
0'	feet to	20'	NEAT CEMENT	<input checked="" type="checkbox"/>	<input type="checkbox"/>
20'	feet to	200'	BENTONITE GROUT	<input checked="" type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>
	feet to			<input type="checkbox"/>	<input type="checkbox"/>

Neat Cement Fluid Weight 15 LBS lbs/gal  
Bentonite Grout 20% % bentonite  
Date Started 12/16/2011  
Date Completed 12/16/2011

RECEIVED  
2012 JAN 17 PM 2:14  
STATE ENGINEERS OFFICE

9 DRILLER'S CERTIFICATION

This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.

Name Hydro Resources-West, Inc.  
Contractor

Address 4975 W. Winnemucca Blvd.  
Contractor

Winnemucca, NV 89445

Nevada contractor's license number issued by the State Contractor's Board 56797

Nevada driller's license number issued by the Division of Water Resources, the on-site driller # 1713

Signed Michele Strother  
By driller performing actual drilling on site or contractor

Date 1/5/2012

(Rev. 05-06) 40.973431°N 117.489878°W NAD27  
USE ADDITIONAL SHEETS IF NECESSARY