STATE OF NEVADA

DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 116420
Permit No. 82382T
Basin 137B

PRINT OR TYPE ONLY

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 70034

1. OWNER Round Mountain Gold Corp. "DW-68"
MAILING ADDRESS P.O. Box 480
Round Mountain, NV. 89045

ADDRESS AT WELL LOCATION Round Mountain Mine, Round Mountain, NV.
Subdivision Name: County: Nye

2. LOCATION SE¼SW¼ Sec19T10N/ R44E
PERMIT/WAIVER NO. 82382-T
Issued by Water Resources Parcel. No.

Latitude
Longitude

UTM E 492510 ☒ NAD 27
N 4283920 ☐ NAD 83/WGS 84

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☒ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Flooded Rev

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Poorly Welded Tuff		0	80	80
Paleozoic Mestasediments		80	890	810
2.375 .050 .145 Slot 780'-840'				

RECEIVED 2013 MAR -1 AM 11:27 STATE ENGINEER'S OFFICE

Date started: January 27, 20 13
Date completed: February 19, 20 13

7. Water Level
Static water level: 75 feet below land surface
Artesian Flow: N/A G.P.M. N/A P.S.I
Water Temperature: Warm °F
Quality: Good

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
35	780	2
38.705729 °N	NAD27	
117.086105 °W		

9. WELL CONSTRUCTION
Depth Drilled 890 Feet Depth Cased 880 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
26 Inches	0 Feet	20 Feet
19 Inches	20 Feet	890 Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
22	86.60	.375	0	20
12.75	33.38	.250	+2	880
2.375	3.65	.145	+2	840

Perforations:
Type of perforation Louvered
Size of perforation .125
From 120 feet to 220 feet
From 380 feet to 860 feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☒ Neat Cement 0 to 90 ☐ Pumped ☒ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured
Gravel Pack: ☒ Yes ☐ No 100 to 890 ☐ Pumped ☒ Poured
Type: 3/4 X 1/2
Bentonite Chips: ☒ Yes ☐ No 90 to 100 ☐ Pumped ☒ Poured
Type: 3/8 Hole Plug

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Boart Longyear (CONTRACTOR)
Address 2745 California Ave. (CONTRACTOR)
SLC., UT.84104
Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2350
Signed
By driller performing actual drilling on site or contractor
Date February 26, 2013