

**STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT**

OFFICE USE ONLY
Log No. 116423
Permit No. 27225
Basin 184

**PRINT OR TYPE ONLY
DO NOT WRITE ON BACK**

*Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340*

NOTICE OF INTENT NO. 68332

1 OWNER Indian Hills General Improvement District ADDRESS AT WELL LOCATION At the end of Impala Drive
MAILING ADDRESS 3394 James Lee Park Road in the Indian Hills Subdivision
SW Carson City, NV, 89705 Subdivision Name Indian Hills County: Douglas

2 LOCATION SE 1/4 27225 14 N/S R 20 E Latitude 39 05.099 N UTM E NAD 27
PERMIT/WAIVER No. 27225 Longitude 119 46.628 W N NAD 83/WGS 84
Issued by Water Resources Parcel No.

3 TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
Is this well being plugged because a replacement well was drilled? _____
If yes, what is replacement well NOI? _____
Is there an existing well log? yes
If yes, what is NDWR well log #? 13999

4 EXISTING WELL CONSTRUCTION
Depth Drilled 250 Feet Depth Cased 250 Feet

| EXISTING CASING SCHEDULE | | | | |
|--------------------------|---------------------|-------------------------|-------------|-----------|
| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
| 8 | | .188 | +1 | 250 |
| | | | | |
| | | | | |

Existing Perforations:

| Type of perforation | Size of perforation | From | To |
|---------------------|---------------------|------|-----|
| torch cut | 0.125 | 168 | 250 |
| | | | |
| | | | |
| | | | |
| | | | |

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why: _____

Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no
If casing was left in place, please show where additional perforations were made:
Additional Perforations:

| Type of perforator used: | From | To | Number of perfs per linear foot |
|--------------------------|------|-----|---------------------------------|
| Mills Knife | 5 | 160 | 4 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

5 WATER LEVEL
Static water level 73' - 45.9' feet below land surface
Artesian flow _____ G.P.M. _____ P.S.I.
Water temperature _____ °F Quality _____

8 WELL PLUGGING MATERIALS

| From | To | Material Used | Notes |
|------|-----|---------------|--|
| 0 | 250 | neat cement | <input checked="" type="checkbox"/> Pumped <input type="checkbox"/> Poured |
| | | | <input type="checkbox"/> Pumped <input type="checkbox"/> Poured |
| | | | <input type="checkbox"/> Pumped <input type="checkbox"/> Poured |
| | | | <input type="checkbox"/> Pumped <input type="checkbox"/> Poured |
| | | | <input type="checkbox"/> Pumped <input type="checkbox"/> Poured |
| | | | <input type="checkbox"/> Pumped <input type="checkbox"/> Poured |

6 Additional Notes or Comments

Removed 210' of 3" drop pipe and pump from well. Measured static water level at 73' and depth of well at 250'. Installed Mills Knife and cut 4 rows per foot from 160' back to 5'. From 48' up, perforator did have resistance due to current cement seal. Removed perforator and installed 2" tremme pipe to 241'. We then pumped in 5 yards of neat cement. Calculated well volume at 4.8 yards with a 1.5 multiplier. The following day, tagged top of cement at 82'. We installed 80' of tremme pipe and mixed 30 bags of Portland cement with approx. 150 gallons of water. We pumped well full to surface. Well actually required 165 cu. Ft. of neat cement.

Neat Cement Fluid Weight 14.2 lbs/gal
Bentonite Grout _____ % bentonite
Date Started 6/26/2012
Date Completed 6/28/2012

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Carson Pump, LLC Contractor
Address P.O. Box 20159 Contractor
Carson City, NV, 89721
Nevada contractor's license number issued by the State Contractor's Board 39920
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2265
Signed [Signature] By driller performing actual drilling on site or contractor
Date 6/30/2012

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY

RECEIVED
39.085075° N
119.776120° W
NAD27