

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 116452
Permit No. 29257/29258
Basin 069

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 68525

1 OWNER WINNEMUCCA FARMS ADDRESS AT WELL LOCATION WINNEMUCCA FARMS
MAILING ADDRESS ONE POTATO RD. WELL #
WINNEMUCCA, NV 89445 Subdivision Name: County: Humboldt

2 LOCATION NE ¼ NE ¼ Sec 30 T 39N N/S R 39 E Latitude 41° 13.978 N UTM E NAD 27
PERMIT/WAIVER No. 29257/29258 Longitude 117° 37.232 W N NAD 83/WGS 84
Issued by Water Resources Parcel No.

3 TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
Is this well being plugged because a replacement well was drilled? YES
If yes, what is replacement well NOI? 68524 Is there an existing well log? YES
If yes, what is NDWR well log #? 15367

4 EXISTING WELL CONSTRUCTION
Depth Drilled 484' Feet Depth Cased 375' Feet

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16"		.250"	0'	375'

Existing Perforations:

Type of perforation	Size of perforation	From	To
JOHNSON SCREEN	0.100"		
		From 109'	feet to 230'
		From 330'	feet to 340'
		From 360'	feet to 365'
		From	feet to
		From	feet to

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why:

Additional Perforations:

Type of perforator used:	From	To	Number of perfs per linear foot
HOLT AIR PERFORATOR	0'	109'	8 Rows
	230'	330'	8 Rows
	340'	360'	8 Rows

5 WATER LEVEL
Static water level 50' feet below land surface
Artesian flow NO G.P.M. 0 P.S.I.
Water temperature COOL °F Quality

8 WELL PLUGGING MATERIALS

From	To	Material Used	Method
0'	50'	NEAT CEMENT	<input checked="" type="checkbox"/> Pumped <input type="checkbox"/> Poured
50'	460'	BENTONITE GROUT	<input checked="" type="checkbox"/> Pumped <input type="checkbox"/> Poured
			<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
			<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
			<input type="checkbox"/> Pumped <input type="checkbox"/> Poured

6 Additional Notes or Comments
plugged log 15367 replaced by 116350

Neat Cement Fluid Weight 15 LBS lbs/gal
Bentonite Grout 20% % bentonite
Date Started 8/22/2012
Date Completed 8/23/2012

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Hydro Resources - West, Inc. Contractor
Address 4975 W. Winnemucca Blvd. Contractor
Winnemucca, NV 89445
Nevada contractor's license number 56797
issued by the State Contractor's Board
Nevada driller's license number issued by the # 2437
Division of Water Resources, the on-site driller
Signed Michelle Atrothey
By driller performing actual drilling on site or contractor
Date 8/29/2012

(Rev 06-06) 41.233066 °N
117.619573 °W NAD27

USE ADDITIONAL SHEETS IF NECESSARY