

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 116459
Permit No. 49612
Basin 129

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 68652

1 OWNER Coeur Rochester
MAILING ADDRESS P.O. Box 1057, Lovelock, NV 89419

ADDRESS AT WELL LOCATION Rochester Mine

2 LOCATION SE 1/4 NW 1/4 Sec 22 T 28N N/S R 34 E
PERMIT/WAIVER No. 49612
Issued by Water Resources Parcel No.

Subdivision Name: County: Pershing
Latitude UTM E 402547 NAD 27
Longitude N 4459159 NAD 83/WGS 84

3 TYPE OF WELL
 Domestic
 Municipal/Industrial
 Irrigation
 Monitor
 Test
 Stock

Is this well being plugged because a replacement well was drilled? Yes
If yes, what is replacement well NOI? 68657

Is there an existing well log? Yes
If yes, what is NDWR well log #? 27854

4 EXISTING WELL CONSTRUCTION
Depth Drilled 1143 Feet Depth Cased 1143 Feet

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16	42	.250	0	107
10-3/4	28	.250	0	1143

If well was not cleaned out to total depth, please explain why:
Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no

Existing Perforations:

From	Type of perforation	To
From 430 - 522	Johnson Hi-cap Screen .08" slot	522
From 542 - 630	Milled dbl std perf 1/8"x3" slot	630
From 650 - 691		691
From 731 - 752		752
From 812 - 832		832

Additional Perforations:

From	Type of perforator used:	To	Number of perfs per linear foot
From		feet	

5 WATER LEVEL
Static water level 480 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

8 WELL PLUGGING MATERIALS

6 Additional Notes or Comments
Existing Perforations (continued from above):
Perf 852 - 892 Scn 892 - 912
912 - 980 980-1120
1120-1140

From	To	Material Used	Pumped	Poured
From 1143	feet to 0 feet	Portland	<input checked="" type="checkbox"/>	<input type="checkbox"/>
From 1197	feet to feet		<input type="checkbox"/>	<input type="checkbox"/>
From	feet to feet		<input type="checkbox"/>	<input type="checkbox"/>
From	feet to feet		<input type="checkbox"/>	<input type="checkbox"/>
From	feet to feet		<input type="checkbox"/>	<input type="checkbox"/>
From	feet to feet		<input type="checkbox"/>	<input type="checkbox"/>

Open annulus between 16" and 10-3/4" casing to 34'.
Tried cleaning hole flooded reverse and hit break in casing at 750' and fluid keeps squeezing off. Switched to mud conventional. Cleaning hole with 8-3/4" tricone.

Neat Cement Fluid Weight 15 lbs/gal
Bentonite Grout % bentonite
Date Started 4/8/2012
Date Completed 4/14/2012

Total of 740' of casing pulled from this well
480' of 10-3/4" blank
140' of 10-3/4" slotted
60' of 10-3/4" wire wrap ss.
60' of 10-3/4" slotted ss.

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.

Original well log unknown
Replacement well log # 116485

Name Boart Longyear Drilling Contractor
Address 2745 W. California Ave. Contractor
Salt Lake City, UT 84104
Nevada contractor's license number issued by the State Contractor's Board 021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1488 4733
Signed Scott Krug By driller performing actual drilling on-site or contractor
Date 9/11/2012

(Rev 05 08)

USE ADDITIONAL SHEETS IF NECESSARY

40.279135°N
118.146313°W NAD27