

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY  
Log No. 116563  
Permit No. 0928  
Basin

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 62099

1 OWNER **Debbie Block**  
MAILING ADDRESS **4272 Dant Blvd**  
**Reno, NV 89509**

ADDRESS AT WELL LOCATION **11690 Sitka St.**  
**Reno, NV 89506**

2 LOCATION NE 1/4 NW 1/4 Sec 22 T 21N N/S/R 19 E  
PERMIT/WAIVER No **080-302-09**  
Issued by Water Resources Parcel No

Subdivision Name: **Lemmon Valley** County: **Washoe**  
Latitude **N39 40.597** UTM E  NAD 27  
Longitude **W119 50.487** N  NAD 83/WGS 84

3 TYPE OF WELL  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

Is this well being plugged because a replacement well was drilled? **No**  
If yes, what is replacement well NO? \_\_\_\_\_  
Is there an existing well log? **No**  
If yes, what is NDWR well log #? \_\_\_\_\_

4 EXISTING WELL CONSTRUCTION  
Depth Drilled **125 Feet** Depth Cased **125 Feet**

7 WELL PLUGGING PROCEDURE  
Was well cleaned out to total depth?  yes  no  
If well was not cleaned out to total depth, please explain why:  
**Well was bailed from 117 feet to 125**

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	12.97	.188	+2	125

Was the well contaminated?  yes  no  
Was the casing pulled?  yes  no  
Was the casing over drilled?  yes  no  
If casing was left in place, please show where additional perforations were made:  
Additional Perforations:

Existing Perforations:

Type of perforation	Size of perforation	From	feet to	feet

Unknown (no log)

Type of perforator used: **Mills Knife**

From	feet to	feet	Number of perfs per linear foot
125	45	45	4

5 WATER LEVEL  
Static water level **76** feet below land surface  
Artesian flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water temperature \_\_\_\_\_ °F Quality \_\_\_\_\_

8 WELL PLUGGING MATERIALS

From	feet to	feet	Material Used	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
125	0	0	Neat Cement	<input checked="" type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>

6 Additional Notes or Comments  
**Remove pump, pipe, wire, and pitless adapter. Bailed out loose sand 117 to 125. Perforate four rows per foot from 125 to 45 (seal) install 2" trim pipe to 124 and pump approximately 4806 lbs of neat cement to surface, cut casing one foot below finish grade to abandon well.**

Neat Cement Fluid Weight **4806 /137.32 lbs/gal**  
Bentonite Grout \_\_\_\_\_ % bentonite  
Date Started **7/18/2012**  
Date Completed **7/18/2012**

RECEIVED  
2012 JUL 23 AM 10:54  
STATE ENGINEERS OFFICE

9 DRILLER'S CERTIFICATION  
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
Name **A.S.A.P Pump and Well Service, LLC.**  
Contractor  
Address **PO Box 60130**  
Contractor  
**Reno, NV 89506**  
Nevada contractor's license number issued by the State Contractor's Board **35387C**  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller **1509**  
Signed **Larry Welch**  
By driller performing actual drilling on site or contractor  
Date **7/19/2012**

USE ADDITIONAL SHEETS IF NECESSARY

39.676708° N  
119.840423° W NAD27