STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 116720
Permit No.
Basin 071

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 69434

1. OWNER Jim McKillop
MAILING ADDRESS 3215 Bruce Drive
WMCA NV 89445

ADDRESS AT WELL LOCATION 6479 Brinkenhoff CT
Subdivision Name: Brinkenhoff County: Humboldt

2. LOCATION SE ¼ NE ¼ Sec 12 T 35 N/S R 37 E
PERMIT/WAIVER No. 13-475-54
Issued by Water Resources Parcel No.

Latitude
Longitude
UTM E 436219 ☒ NAD 27
N 4530356 ☐ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top Soil		0	3	3
Rocky Clay		3	20	17
Big Gravel + Sand		20	60	40
Sandy Clay		60	80	20
Sand + Gravel + Clay		80	100	20
Soft Rocky Clay		100	160	40

RECEIVED
2013 MAY 31 AM 10:51
STATE ENGINEERS OFFICE

NAD 27
40.923748°N
117.757485°W

Date started: 5-2, 20 13
Date completed: 5-4, 20 13

9. WELL CONSTRUCTION
Depth Drilled 160 Feet Depth Cased 160 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
10 5/8 Inches	0 Feet	160 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	+1 1/2	160

Perforations:
Type of perforation Sawed (PVC)
Size of perforation 3/16 X 3
From 120 feet to 160 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☐ Concrete Grout 5 to 60 ☐ Pumped ☒ Poured
☐ ≥80% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ☒ Yes ☐ No 100 to 160 ☐ Pumped ☒ Poured
Type: 3/8 -
Bentonite Chips: ☒ Yes ☐ No 60 to 100 ☐ Pumped ☒ Poured
Type: 3/8

7. Water Level
Static water level: 73 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: Cold °F
Quality: Good

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Rotary	75x	UNK	2 Hrs

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name LBJ DRILLING & PUMP COMPANY, INC.
Contractor
Address P.O. BOX 902 - Winnemucca, NV 89446
Contractor

Nevada contractor's license number issued by the *State Contractor's Board* 0009605A
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1807

Signed Joe Boggio
By driller performing actual drilling on-site or contractor Joe Boggio
Date

(Rev 06-08)

USE ADDITIONAL SHEETS IF NECESSARY