STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 116747
Permit No.
Basin 1378

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form it its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 33055

1. OWNER ROUND MOUNTAIN GOLD
MAILING ADDRESS PO BOX 480
ROUND MOUNTAIN, NV 89045

ADDRESS AT WELL LOCATION ROUND MOUNTAIN
MINE SITE - NEAR ROUND MOUNTAIN NEVADA

2. LOCATION SW ¼ SE ¼ Sec 24 T 10N N/S R 43 E
PERMIT/WAIVER No. M/O 1813 *Issued by Water Resources* Parcel No.

Latitude
Longitude
UTM E 491701.4 ☑ NAD 27
N 4283899.0 ☐ NAD 83/WGS 84
Subdivision Name: N/A *County:* Nye

3. WORKED PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other...

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☑ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☑ Other... CORE

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
ALLUVIUM		0	924	924
TUFF		924	1089	165
SANDSTONE/SILTSTONE		1089	1211	122
TUFF		1211	1262	51
SANDSTONE/SILTSTONE		1262	1282	20
DENSELY WELDED TUFF		1282	1970	688
POORLY WELDED TUFF		1970	2185	215
PEZOMETER SET AT 1282'				
SOLID CORE FIBERGLASS				
SACRIFICIAL ROD TO SET				
PEZOMETER.. GROUT HOLE				
BOTTOM TO SURFACE -				
SOLID CORE				
HOLE # D-542				

well name

Date started 4/15/2012 , 20 12
Date completed 5/7/2012 , 20 12

RECEIVED 2012 MAY 29 PM 1:57 STATE ENGINEERS OFFICE

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 2185 Feet Depth Cased 1254 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
5 1/2	Inches	0	Feet	205	Feet
4 1/2	Inches	205	Feet	1254	Feet
3.875	Inches	1254	Feet	2185	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
5 1/2	14.4	.250	0	205
4 1/2	11.7	.250	0	1254

Perforations:
Type of perforation
Size of perforation
From feet to feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 0 - 2185
Placement Method: ☑ Pumped ☐ Poured
Seal Type: ☑ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Gravel Packed: ☐ Yes ☑ No
From feet to.. feet

9. WATER LEVEL
Static water level N/A feet below land surface
Artesian flow G.P.M P.S.I
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name NATIONAL EWP (Contractor)
Address 580 W. SILVER ST. (Contractor)
ELKO, NV 89801
Nevada contractor's license number issued by the *State Contractor's Board* 0075355
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* M-2215
Signed (By driller performing actual drilling on site or contractor)
Date 5/7/2012

(Rev. 06/10)

38.705550 °N
117.095439 °W
NAD27

USE ADDITIONAL SHEETS IF NECESSARY