STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 116925
Permit No.
Basin No. 028

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 70207
WELL NAME *(If applicable)* MW-AG

1. OWNER/CLIENT NAME Hycroft Resources & Development
MAILING ADDRESS P.O. Box 3030 Winnemucca, NV 89445

DETAILED ADDRESS AT WELL LOCATION Hycroft Mine
Well ID # 4862
Subdivision Name. *County:* Pershing

2. PLS LOCATION NE ¼ NE ¼ 12 Sec 34 N/S 28 E
PERMIT/WAIVER NO. MO-1890 *Issued by Water Resources* *Current Parcel No.*

Latitude 40* 49.928 N UTM E ☐ NAD 27
Longitude 118* 46.809 W UTM N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☒ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☐ Rotary ☐ RVC
☐ Air ☒ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To	Thickness
Sand			0'	15'	15'
Gravel with Clay			15'	130'	115'
Silty Sand			130'	420'	290'
This borehole did not look good so we plugged it to state regs. and put a 20' neat cement cap on it.					
NAD27					
40, 832302° N					
118, 779151° W					

Date started: 17-Jun, 20 13
Date completed: 18-Jun, 20 13

9. WELL CONSTRUCTION
Depth Drilled: 420' Feet Depth Cased: 0' Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
13"	Inches	0'	Feet	20'	Feet
7 7/8"	Inches	20'	Feet	420'	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8 5/8"		.188"	0'	20'

PERFORATIONS:
Type of perforation: N/A
Size of perforation:
From Feet To Feet
From Feet To Feet
From Feet To Feet

ANNULAR MATERIALS

☒ Sanitary Seal	0' to 20'			
☒ Neat Cement	0' to 20'	☒ Pumped	☐ Poured	
☐ Cement Grout	to	☐ Pumped	☐ Poured	
☐ Concrete Grout	to	☐ Pumped	☐ Poured	
☐ Bentonite Chips	to	☐ Pumped	☐ Poured	
☒ Bentonite Grout	20' to 420'	☒ Pumped	☐ Poured	
☐ 15 % ☐ 20 % ☒ Other, explain: 30%				
☐ Gravel Pack [> 0.2 in.]	to	☐ Pumped	☐ Poured	
☐ Sand Pack [< 0.2 in.]	to	☐ Pumped	☐ Poured	
☐ Other, explain:	to	☐ Pumped	☐ Poured	

7. WATER QUALITIES
Static water level: N/A Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: ° Fahrenheit
Water Quality:

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name Hydro Resources-West, Inc. *Contractor*
Address 4975 W. Winnemucca Blvd. Winnemucca, NV 89445 *Contractor*
Nevada contractor's license number as issued by the *State Contractor's Board:* 56797
Nevada well driller's license number as issued by the *Nevada Division of Water Resources (on-site driller):* # 1713
Signed: Michelle Strother *By driller performing actual drilling on site or contractor*
Date: 7/2/13

(Rev. 08-12)
USE ADDITIONAL SHEETS IF NECESSARY