



Time	PID Reading (ppmv)	Blow Count (per 6 inches)	Sample Number	Sample Interval	Depth (ft)	DESCRIPTION OF SUBSURFACE MATERIALS		Well Construction
						Lithology	Borehole Location: by RW-1 & SV-2 Total Depth: 23' Depth to Bedrock: Depth to Water: ~11' Groundwater Elevation (MSL):	
12:30					0-5	Fill	4" asphalt pavement over gravelly sand, brown	
					5-7.5	SM	SILTY SAND - w/gravel, brown	
					7.5-10	CAL	CALICHE - HARD tan	
					10-10.5	CL	Gravelly clay - w/caliche lenses, str. hydro odor - gray	
13:20	>5000	48	RW-5 @ 10'	9.5-10.5'	10-15	CL	SANDY CLAY - w/mod. odor, gray	
					15-20	CAL	CALICHE - mod. hard gray	
					20-23	CL	SANDY CLAY - w/gravel, gray wet	
					23		Be 23'	
15:30					25			

Date Started/Completed: March 6, 2013	Logged by: T. Aten
Drilling Agency/Driller: Eagle	Checked by: Keith Stewart
Equipment Used: Dietrich D120	Comments:
Drilling Method/Fluid: HSA	STEWART ENVIRONMENTAL, INC.
Hammer Weight/Drop Distance: 140 lb	File No.: 07-515.11
Borehole Diameter: 10"	LOG OF BORING NO.: RW-5
Completion: 4" remediation well	Page 1 of 1

4" screen .020 slot 8' to 23'  
 4" casing 1' to 8'  
 #12 sand 7.5' to 23'  
 bent. seal 4' to 7.5'  
 concrete 2' to 4'

Lat: 36.11425 N  
 Long: 115.16338 W

DCNR/DWR/SNBO  
 RECEIVED  
 MAR 27 2013