

mw - 8

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 117303
Permit No.
Basin 067

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 69203
1600 National Guard Way
Reno, NV
County: WASHOE

1 OWNER AVIS BUDGET CAR RENTAL
MAILING ADDRESS 6 SYLVAN WAY
PARSIPPANY, NJ 07054

ADDRESS AT WELL LOCATION

2 LOCATION SE 1/4 NW 1/4 Sec 19 T 19N N/S R 20 E
PERMIT/WAIVER No.

Subdivision Name:
Latitude 48538.49.30 UTM E 260880.08 NAD 27
Longitude 2286757.74 N 4375631.62 NAD 83/WGS 84

3 TYPE OF WELL
 Domestic
 Municipal/Industrial
 Irrigation
 Monitor
 Test
 Stock

Is this well being plugged because a replacement well was drilled? NO
Is there an existing well log?
If yes, what is NDWR well log #?

4 EXISTING WELL CONSTRUCTION
Depth Drilled 20 Feet
Depth Cased 20 Feet

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why:

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2	12	.154	.5	20
Sched 40	PVC			

Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no
If casing was left in place, please show where additional perforations were made:
Additional Perforations:
Type of perforator used:

Existing Perforations:
Type of perforation Machine cut
Size of perforation .070
From 10 feet to 20 feet

From	feet to	feet	Number of perfs per linear foot
From	feet to	feet	Number of perfs per linear foot
From	feet to	feet	Number of perfs per linear foot
From	feet to	feet	Number of perfs per linear foot
From	feet to	feet	Number of perfs per linear foot
From	feet to	feet	Number of perfs per linear foot

5 WATER LEVEL
Static water level 8 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

8 WELL PLUGGING MATERIALS
Material Used
From 0 feet to 20 feet neat cement Pumped Poured

6 Additional Notes or Comments
Placed drill rod inside 2" PVC casing, over drilled casing with HSA, pulled casing, used HSA to trim it, neat cement

Neat Cement Fluid Weight lbs/gal
Bentonite Grout % bentonite
Date Started 5/29/13
Date Completed 5/29/13

REC'D BY: [illegible]
DATE: JUL 30 2013
ENGINEERS OFFICE
Plugs unknown well log NAD 27 39.4989510 N 119.7509186 W

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Gregg Drilling Contractor
Address 950 Howe Rd Contractor Martinez, CA 94553
Nevada contractor's license number issued by the State Contractor's Board C23-0038113
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2322 M
Signed [Signature]
Date 6/16/13