

**ORIGINAL**

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
**WELL DRILLER'S PLUGGING REPORT**

OFFICE USE ONLY	
Log No.	1173510
Permit No.	
Basin	070

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 67747

1 OWNER CITY OF WINNEMUCCA  
 MAILING ADDRESS 90 WEST 4TH STREET  
WINEMUCCA, NV 89445

ADDRESS AT WELL LOCATION WINNEMUCCA AIRPORT  
EAST WELL  
 Subdivision Name: \_\_\_\_\_ County: Humboldt

2 LOCATION SW 1/4 SE 1/4 Sec 15 T 35N N/S R 37 E  
 PERMIT/WAIVER No. N/A  
Issued by Water Resources Parcel No.

Latitude 40° 54.234 N UTM E  NAD 27  
 Longitude 117° 48.136 W N  NAD 83/WGS 84

3 TYPE OF WELL  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

Is this well being plugged because a replacement well was drilled? NO  
 If yes, what is replacement well NOI? \_\_\_\_\_  
 Is there an existing well log? YES  
 If yes, what is NDWR well log #? 936

4 EXISTING WELL CONSTRUCTION  
 Depth Drilled 159' Feet Depth Cased 159' Feet

7 WELL PLUGGING PROCEDURE  
 Was well cleaned out to total depth?  yes  no  
 If well was not cleaned out to total depth, please explain why: \_\_\_\_\_

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8"		.188"	0'	159'

Was the well contaminated?  yes  no  
 Was the casing pulled?  yes  no  
 Was the casing over drilled?  yes  no  
 If casing was left in place, please show where additional perforations were made:  
 Additional Perforations: \_\_\_\_\_

Existing Perforations:

Type of perforation	MILLS KNIFE			
Size of perforation	From	feet to	feet	feet
	126'	feet to	159'	feet
		feet to		feet
		feet to		feet
		feet to		feet
		feet to		feet

Type of perforator used: HOLT AIR PERFORATOR

From	feet to	feet	Number of perfs per linear foot
5'	feet to	130'	4 ROWS
	feet to		

5 WATER LEVEL  
 Static water level 55' feet below land surface  
 Artesian flow NO G.P.M. 0 P.S.I.  
 Water temperature COOL °F Quality \_\_\_\_\_

8 WELL PLUGGING MATERIALS

Material Used			
From 0'	feet to 20'	NEAT CEMENT	<input checked="" type="checkbox"/> Pumped <input type="checkbox"/> Poured
From 20'	feet to 159'	BENTONITE GROUT	<input checked="" type="checkbox"/> Pumped <input type="checkbox"/> Poured
From	feet to		<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
From	feet to		<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
From	feet to		<input type="checkbox"/> Pumped <input type="checkbox"/> Poured

6 Additional Notes or Comments

Plugs well log # 936

40.903996° N NAD 27  
 117.801302° W Dec 1 Deg

Neat Cement Fluid Weight 15 LBS lbs/gal  
 Bentonite Grout 20% % bentonite  
 Date Started 11/19/2011  
 Date Completed 11/19/2011

9 DRILLER'S CERTIFICATION  
 This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
 Name Hydro Resources - West Contractor  
 Address 4975 W. Winnemucca Blvd. Contractor  
Winnemucca, NV 89445  
 Nevada contractor's license number issued by the State Contractor's Board 56797  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller # 1713  
 Signed Michelle Strother By driller performing actual drilling on site or contractor  
 Date 12/7/11