

**ORIGINAL**

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
**WELL DRILLER'S PLUGGING REPORT**

OFFICE USE ONLY  
Log No. 117652  
Permit No. 25948  
Basin 0109

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 67088

1 OWNER WINNEMUCCA FARMS ADDRESS AT WELL LOCATION WELL # 19  
 MAILING ADDRESS One Potato Rd  
NW Winnemucca, NV 89445 *Subdivision Name:* \_\_\_\_\_ *County:* Humboldt

2 LOCATION NE 1/4 Sec 6 T 38N N/S R 39 E Latitude 41° 12.271 N UTM E  NAD 27  
 PERMIT/WAIVER No. 25948 Longitude 117° 37.771 W N  NAD 83/WGS 84  
*issued by Water Resources Parcel No.* \_\_\_\_\_

3 TYPE OF WELL Is this well being plugged because a replacement well was drilled? Is there an existing well log?  
 Domestic  Irrigation  Test YES  
 Municipal/Industrial  Monitor  Stock If yes, what is replacement well NOI? 66069 If yes, what is NDWR well log #? 12797

4 EXISTING WELL CONSTRUCTION  
 Depth Drilled 454' Feet Depth Cased 445' Feet

EXISTING CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16"		.250"	0'	445'

7 WELL PLUGGING PROCEDURE  
 Was well cleaned out to total depth?  yes  no  
 If well was not cleaned out to total depth, please explain why: \_\_\_\_\_  
 Was the well contaminated?  yes  no  
 Was the casing pulled?  yes  no  
 Was the casing over drilled?  yes  no  
 If casing was left in place, please show where additional perforations were made:  
*Additional Perforations:*

Existing Perforations:

Type of perforation	WIRE WRAP SCREEN			
Size of perforation	N/A			
From 189'	feet to	194'	feet	
From 198'	feet to	208'	feet	
From 222'	feet to	227'	feet	
From 236'	feet to	241'	feet	
From 244'	feet to	249'	feet	

*Type of perforator used:* **HOLT AIR PERFORATOR**

From	feet to	feet	Number of perfs per linear foot	
From 11'	feet to	189'	feet	6 Rows
From 194'	feet to	198'	feet	6 Rows
From 208'	feet to	222'	feet	6 Rows
From 227'	feet to	236'	feet	6 Rows
From 249'	feet to	305'	feet	6 Rows
From	feet to	feet	Number of perfs per linear foot	

5 WATER LEVEL  
 Static water level 91' feet below land surface  
 Artesian flow NO G.P.M. 0 P.S.I.  
 Water temperature COOL °F Quality \_\_\_\_\_

8 WELL PLUGGING MATERIALS

Material Used			
From 0'	feet to 50'	feet	NEAT CEMENT <input checked="" type="checkbox"/> Pumped <input type="checkbox"/> Poured
From 50'	feet to 445'	feet	BENTONITE GROUT <input checked="" type="checkbox"/> Pumped <input type="checkbox"/> Poured
From	feet to	feet	<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
From	feet to	feet	<input type="checkbox"/> Pumped <input type="checkbox"/> Poured
From	feet to	feet	<input type="checkbox"/> Pumped <input type="checkbox"/> Poured

6 Additional Notes or Comments

ADDITIONAL EXISTING PERFORATIONS

305' - 310'  
328' - 333'  
342' - 347'  
356' - 361'  
368' - 378'  
397' - 402'  
421' - 426'

Neat Cement Fluid Weight 15 LBS lbs/gal  
 Bentonite Grout 20% % bentonite  
 Date Started 5/3/2012  
 Date Completed 5/5/2012

THIS WELL WAS COLLAPSED AT 315'. WE DID NOT RUN OUR PERFORATOR PAST THIS POINT.

RECEIVED  
 2012 JUL 13 AM 10:09  
 STATE ENGINEERS OFFICE

9 DRILLER'S CERTIFICATION  
 This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.

Name Hydro Resources - West, Inc.  
 Contractor  
 Address 4975 W. Winnemucca Blvd.  
 Contractor  
Winnemucca, NV 89445

Nevada contractor's license number \_\_\_\_\_  
 issued by the State Contractor's Board 56797  
 Nevada driller's license number issued by the \_\_\_\_\_  
 Division of Water Resources, the on-site driller # 2437

Signed Michele Strother  
 By driller performing actual drilling on site or contractor  
 Date 7/10/2012

USE ADDITIONAL SHEETS IF NECESSARY

NAD 27 41.208616° N  
 117.628556° W