STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 117653
Permit No.
Basin 072

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 67096

1. OWNER Travel Centers of America
MAILING ADDRESS 24601 Center Ridge Rd Ste 200 Westlake, Ohio 44145
ADDRESS AT WELL LOCATION Travel Centers Truck Stop 6000 E. Frontage Rd, Mill City NV 89418
Subdivision Name:
County: Pershing

2. LOCATION NW ¼ NW ¼ Sec 33 T 33 0/S R 35 E
PERMIT/WAIVER No. 5-000016 Issued by Water Resources
003-130-01 Parcel No.
Latitude N 40.69362°
Longitude W 118.057070°
UTM E
N
☐ NAD 27 ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition ☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test ☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC ☐ Air ☒ Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Silt, Sand, Gravel	no	0	20	20
Silt Sand	no	20	45	25
Silt Sand Gravel	yes	45	65	20
Sand Gravel	yes	65	75	10

MW-10

RECEIVED 2012 MAR 14 AM 10:43 NV DIV OF WATER RESOURCES

Date started: 2/7, 20 12
Date completed: 2/7, 20 12

7. Water Level
Static water level: 60' feet below land surface
Artesian Flow: no G.P.M. P.S.I.
Water Temperature: <85 °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

9. WELL CONSTRUCTION
Depth Drilled 75 Feet Depth Cased 75 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
8"	Inches	0	Feet	75	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2"		Schedule 40	0	45

Perforations:
Type of perforation Factory Slot
Size of perforation .020
From 45 feet to 75 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☒ Neat Cement 0 to 33 ☒ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ☒ Yes ☐ No 43 to 75 ☐ Pumped ☒ Poured
Type: 10/20 silica sand
Bentonite Chips: ☒ Yes ☐ No 33 to 43 ☐ Pumped ☒ Poured
Type: 3/8 Bentonite Chips

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name HAZ-Tech Drilling (Contractor)
Address P.O. Box 940 (Contractor)
Meridian, Id 83680
Nevada contractor's license number issued by the State Contractor's Board 0038018
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2412 M-LTD
Signed (By driller performing actual drilling on-site or contractor)
Date 2/14/12

(Rev. 05.06)

USE ADDITIONAL SHEETS IF NECESSARY

NAD 27 40.693,715°N
118.056,097°W

(NSPO 3-08)

(O) 627