STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 117841
Permit No.
Basin 087

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 69060

1. OWNER 7-Eleven Inc.
MAILING ADDRESS P.O. Box 711
Dallas, TX 75221

ADDRESS AT WELL LOCATION 1680 Silverada Blvd.
Reno, NV 89572
Subdivision Name: N/A County: Washoe

2. LOCATION SE ¼ NW ¼ Sec 6 T 19 N/S R 20 E
PERMIT/WAIVER No. 4-000379 (Issued by Water Resources) 008-073-01 (Parcel No.)

Latitude N 39.54443°
Longitude W 119.78239°
UTM E
N
☐ NAD 27 ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition ☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test ☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC ☒ Air ☐ Other

6. LITHOLOGIC LOG MW8

Material	Water Strata	From	To	Thickness
A/C		0	5"	5"
Air Knife clayey sand (SC)		5"	5"	4'7"
Lt grey well graded gravel w/ sand (GW) dry		5"	32.5"	27.5"
brown silty gravel (GM) w/ sand moist		32.5"	37"	4.5"
brown silty gravel (GM) w/ sand sat.	37	37	46"	9'

RECEIVED 2012 DEC 18 AM 11:21 STATE ENGINEERS OFFICE

Date started: 12-3, 20 12
Date completed: 12-5, 20 12

7. Water Level
Static water level: 37 feet below land surface
Artesian Flow: No G.P.M. - P.S.I.
Water Temperature: - °F
Quality: -

8. N/A WELL TEST DATA N/A
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

9. WELL CONSTRUCTION
Depth Drilled 46 Feet Depth Cased 45½ Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
8	Inches	46	Feet	0	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4"		sch 40	45½	½

Perforations:
Type of perforation 0.020
Size of perforation slotted screened
From 45 feet to 25 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☒ Neat Cement 22 to 1 ☒ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☒ Concrete Grout 1 to 0 ☐ Pumped ☒ Poured
☐ ≥80% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ☒ Yes ☐ No 45½ to 24 ☐ Pumped ☒ Poured
Type: Cemex Lapis Lustre #3
Bentonite Chips: ☒ Yes ☐ No 24 to 22 ☐ Pumped ☒ Poured
Type: Pure Gold med. chips

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name (Contractor) Dale Lehman
Address (Contractor) 520 Edison Way
Reno NV 89502
Nevada contractor's license number issued by the State Contractor's Board Cascade #73966
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1976
Signed Dale Lehman (By driller performing actual drilling on site or contractor)
Date 12/12/12

(Rev. 05-08)
USE ADDITIONAL SHEETS IF NECESSARY

NAD27 39.544519°N, 119.781367°W