

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S REPORT

OFFICE USE ONLY  
Log No. 117843  
Permit No. \_\_\_\_\_  
Basin 087

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 69060

1. OWNER 7-Eleven Inc. ADDRESS AT WELL LOCATION 1680 Silverada Blvd.  
MAILING ADDRESS P.O. Box 711 Reno NV 89572  
Dallas TX 75221 Subdivision Name: N/A County: Washoe  
2. LOCATION SE 1/4 NW 1/4 Sec 6 T 190 N R 20 E Latitude N 39.54449° UTM E  NAD 27  
PERMIT/WAIVER No. 4-000379 008-073-01 Longitude W 119.78261° N  NAD 83/WGS 84  
Issued by Water Resources Parcel No. \_\_\_\_\_

3. WORKED PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Other  
4. PROPOSED USE  
 Domestic  Irrigation  Test  Cable  Rotary  RVC  
 Municipal/Industrial  Monitor  Stock  Air  Other

6. LITHOLOGIC LOG MW 7

Material	Water Strata	From	To	Thick-ness
<u>A/C</u>		<u>0</u>	<u>5"</u>	<u>5"</u>
<u>Air knife to 5'</u>				
<u>brown clayey sand (sc)</u>		<u>5"</u>	<u>5'</u>	<u>4'7"</u>
<u>brown poorly graded sand (SP) moist</u>		<u>5'</u>	<u>15'</u>	<u>10'</u>
<u>grey well graded gravel (GW) w/ sand dry</u>		<u>15'</u>	<u>30'</u>	<u>15'</u>
<u>grey well graded gravel (GW) w/ sand moist</u>		<u>30'</u>	<u>35'</u>	<u>5'</u>
<u>grey well graded gravel (GW) w/ sand sat.</u>	<u>37'</u>	<u>35'</u>	<u>45'</u>	<u>10'</u>
<u>grey poorly graded sand (SP) sat.</u>		<u>45'</u>	<u>46'</u>	<u>1'</u>

9. WELL CONSTRUCTION  
Depth Drilled 46 Feet Depth Cased 43 Feet  
HOLE DIAMETER (BIT SIZE)  
From 8 Inches 46 Feet 0 Feet  
Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>4</u>		<u>sch 40</u>	<u>43</u>	<u>1/2</u>

Perforations:  
Type of perforation 0.020  
Size of perforation slotted screened  
From 42 1/2 feet to 22 1/2 feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Annular Seal:  Yes  No  
 Neat Cement 20 to 1  Pumped  Poured  
 Cement Grout \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 Concrete Grout 1 to 0  Pumped  Poured  
 ≥80% Bentonite Grout \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
Gravel Pack:  Yes  No 43 to 22  Pumped  Poured  
Type: Cemex Lapis Lustre # 3  
Bentonite Chips:  Yes  No 22 to 20  Pumped  Poured  
Type: Pure Gold Med. chips

Date started: 12/6 20 12  
Date completed: 12/7 20 12

7. Water Level  
Static water level: 37 feet below land surface  
Artesian Flow: N/A G.P.M. \_\_\_\_\_ P.S.I. \_\_\_\_\_  
Water Temperature: \_\_\_\_\_ °F  
Quality: \_\_\_\_\_

8. N/A WELL TEST DATA

TEST METHOD: <input type="checkbox"/> Baller <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name Dale Lehman Contractor  
Address 520 Edison Way Contractor  
Reno NV 89502  
Nevada contractor's license number Cascade  
issued by the State Contractor's Board Drilling # 73966  
Nevada driller's license number issued by the M-1976  
Division of Water Resources, the on-site driller  
Signed Dale Lehman  
By driller performing actual drilling on site or contractor  
Date 12/12/12

RECEIVED  
2012 DEC 18 AM 11:21  
STATE ENGINEERS OFF

USE ADDITIONAL SHEETS IF NECESSARY

NAD 27 39.544579°N, 119.781587°W