

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S REPORT

OFFICE USE ONLY  
Log No. 117844  
Permit No. \_\_\_\_\_  
Basin D87

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 69060

1. OWNER 7-Eleven Inc. ADDRESS AT WELL LOCATION 1680 Silverada Blvd.  
MAILING ADDRESS P.O. Box 711 Reno NV 89572  
Dallas TX 75221 Subdivision Name: N/A County: Washoe

2. LOCATION S2 1/4 NW 1/4 Sec 6 T 19 N R 20 E Latitude N 39.54443° UTM E  NAD 27  
PERMIT/WAIVER No. 4-000379 1008-073-01 Longitude W 119.78264° N  NAD 83/WGS 84

Issued by Water Resources Parcel No. \_\_\_\_\_

3. WORKED PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Other

4. PROPOSED USE  
 Domestic  Irrigation  Test  Stock  
 Municipal/Industrial  Monitor

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other

6. LITHOLOGIC LOG MW 6

Material	Water Strata	From	To	Thick-ness
<u>A/C</u>		<u>0</u>	<u>5"</u>	<u>5"</u>
<u>At Knife to 5'</u>		<u>5"</u>	<u>5'</u>	<u>4'7"</u>
<u>brown clayey sand (SC) moist</u>				
<u>dark brown well graded</u>				
<u>gravel (GW) w/sand dry</u>		<u>5'</u>	<u>15'</u>	<u>10'</u>
<u>brown well graded sand</u>				
<u>(SW) w/silt dry</u>		<u>15'</u>	<u>20'</u>	<u>5'</u>
<u>well graded blk gravel</u>		<u>20'</u>	<u>25'</u>	<u>5'</u>
<u>w/silt + sand (GM) dry</u>				
<u>well graded gravel w/silt</u>	<u>37</u>	<u>25'</u>	<u>40'</u>	<u>15'</u>
<u>and sand (GM) moist</u>				
<u>dark grey poorly graded</u>		<u>40'</u>	<u>45'</u>	<u>5'</u>
<u>gravel (GP) sat.</u>				
<u>brown clayey sand (SC)</u>		<u>45'</u>	<u>46'</u>	<u>1'</u>
<u>SAT.</u>				

9. WELL CONSTRUCTION  
Depth Drilled 46 Feet Depth Cased 44 1/2 Feet

HOLE DIAMETER (BIT SIZE)

	From	To	Feet	Feet
<u>8</u> Inches	<u>46</u>	<u>0</u>		
Inches				
Inches				

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>4</u>		<u>sch 40</u>	<u>44 1/2</u>	<u>1/2</u>

Perforations:

Type of perforation slotted screened

Size of perforation 0.020

From 44 feet to 24 feet

From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Annular Seal:  Yes  No

Neat Cement 22 to 1  Pumped  Poured

Cement Grout \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured

Concrete Grout 1 to 0  Pumped  Poured

≥80% Bentonite Grout \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured

Gravel Pack:  Yes  No 44 1/2 to 24  Pumped  Poured

Type: Cemex Lap's Lustre #3

Bentonite Chips:  Yes  No 24 to 22  Pumped  Poured

Type: Pure Gold Med. Chips

7. Water Level

Static water level: 37 feet below land surface

Artesian Flow: NO G.P.M. \_\_\_\_\_ P.S.I. \_\_\_\_\_

Water Temperature: \_\_\_\_\_ °F

Quality: \_\_\_\_\_

8. N/A WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			

10. DRILLER'S CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Dale Letman Contractor

Address 520 Edison Wky Contractor

Reno NV 89502

Nevada contractor's license number Cascade

issued by the State Contractor's Board Drilling # 73966

Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1976

Signed Dale Letman By driller performing actual drilling on site or contractor

Date 12/12/12

(Rev. 05-06) USE ADDITIONAL SHEETS IF NECESSARY

NAD87 39.544519°N, 119.781617°W

RECEIVED  
2012 DEC 18 AM 11:27  
STATE ENGINEERS OFFICE