STATE OF NEVADA
DIVISION OF WATER RESOURCES
# WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 117957
Permit No.
Basin 202

**PRINT OR TYPE ONLY**
**DO NOT WRITE ON BACK**

*Please complete this form it its entirety in accordance with NRS 534.170 and NAC 534.340*

NOTICE OF INTENT NO. 69488

1. OWNER Kalin Brown
MAILING ADDRESS PO Box 745
Pioche, NV 89043

ADDRESS AT WELL LOCATION 546 Six Mile Well Rd
Pioche, NV 89043

2. LOCATION SW ¼ SW ¼ Sec 22 T 02N N/S R 67 E
PERMIT/WAIVER No. 006-201-20
Issued by Water Resources — Parcel No.

Latitude N 38.011616
Longitude W114.463323
UTM E
N
☐ NAD 27 ☑ NAD 83/WGS 84
Subdivision Name: County: Lincoln

3. WORKED PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other...

4. PROPOSED USE
☑ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☑ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other...

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| Brown Clay | | 0 | 22 | 22 |
| Gravel & Sand | | 22 | 25 | 3 |
| Clay w/sand stringers | | 25 | 49 | 24 |
| Gravel w/cobbles | X | 49 | 53 | 4 |
| Clay w/sand stringers | | 53 | 74 | 21 |
| Gravel & Sand | | 74 | 79 | 5 |
| Clay w/sand stringers | | 79 | 85 | 6 |
| Gravel | X | 85 | 87 | 2 |
| Clay w/sand stringers | | 87 | 113 | 26 |
| Gravel | | 113 | 122 | 9 |
| Clay w/sand stringers | | 122 | 187 | 65 |
| Gravel & Sand | X | 187 | 196 | 9 |
| Clay w/sand stringers | | 196 | 200 | 4 |

NAD27
38.011654°N
114.462493°W

Date started 27-May, 20 13
Date completed 6-Jun, 20 13

7. WELL TEST DATA
TEST METHOD: ☑ Bailer ☐ Pump ☐ Air Lift

| | G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|---|
| Bailer | 15 | 12 | 2 |

8. WELL CONSTRUCTION
Depth Drilled 200 Feet Depth Cased 200 Feet

HOLE DIAMETER (BIT SIZE)

| | | From | | To | |
|---|---|---|---|---|---|
| 12 | Inches | 0 | Feet | 55 | Feet |
| 10 | Inches | 55 | Feet | 200 | Feet |
| | Inches | | Feet | | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 6.625 | | Sched 40 PVC | 3 | 200 |
| 6.625 | | 1/4" steel | +2 | 3 |
| | | | | |

Perforations:
Type of perforation factory horizontal slot
Size of perforation .067 inch
From 100 feet to 200 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 71 ft
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☑ Concrete Grout
Gravel Packed: ☑ Yes ☐ No
From 71 feet to 200 feet

9. WATER LEVEL
Static water level 60 feet below land surface
Artesian flow G.P.M P.S.I
Water temperature cold °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Bevan Lister, 8-Mile Well Service, LLC (Contractor)
Address PO Box 124 (Contractor)
Pioche, NV 89043
Nevada contractor's license number issued by the State Contractor's Board 076655
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2294
Signed Bevan Lister (By driller performing actual drilling on site or contractor)
Date 12-Aug-13

(Rev. 06/10)

**USE ADDITIONAL SHEETS IF NECESSARY**