

CTMRD PROGRAM MONITORING WELL STRATIGRAPHIC LOG

262811 # 707

Drilling Specifications:

Drilling Contractor: Cascade
 Drilling Method: Hand Aug 0-5'
 Rig: Sonic 5-11'
 Driller: Ken Williams
 Boring Diam.: 6 in TD: 11 ft
 Development Method: —
 Date Start: 9/30/13 End: 10/1/13

Well Specifications:

Location Description: East side of Holbrook, 100' N. of Arroyo
 Coordinates: _____ ft N _____ ft E
 Elevation: _____ ft Survey Method: _____
 Reference Pt. Description: _____
 Well TD: 10 ft bgs Well Diameter: 2 in
 Screen Interval: 5-10 ft bgs
 First Water: _____ ft bgs
 Static Water at completion: _____ ft bgs



WELL ID: WP-18
 Project: Vassar East Plumb PSA
 Page 1 of 1
 LOGGED BY: B. Vassar

Depth	Engineering Properties					1 st Description							2 nd Effects		Depositional Properties					Graphics		Description				
	Density/Consistency	Moisture	Plasticity	Cohesiveness	Transmissivity	Color	Boulder %	Cobble %	Gravel %	Sand %	Silt %	Clay %	USCS Classification	Weathering/Oxidization	Grading	Angularity	Matrix/Clast-Supported	Clast Lithology	Sedimentary Structure	Depositional Environment	Stratigraphic Contact		PO/Samples (ppm)	Lithology		
0																										
5																										
10	L	M	LP	C	M	10YR	10	20	20	20	20	GM	WX	WG	R-SR	MXA	G-60 A-40 M			G		0.3				
15																										
20																										
25																										
30																										

Note: Description section to be used to complement and provide additional information to supplement column descriptors to the left. Identify any samples collected, and describe any particulars associated with drilling behavior.

12" asphalt, 6" fill
 date brown silty gravel w/ sand, incl cobbles & boulders 2-4" in in granitic clasts (decomposition)
 greenish brn. silty gravel w/ sand (m-v), incl. cobbles (3-5") & tr. boulders, marked incr. w. gravel, some clasts show weathering rinds & decomposition

STATE ENGINEERS OFFICE
 15:11:51
 2013 OCT 18 AM 10:01:02
 RECEIVED