

**STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT**

OFFICE USE ONLY
Log No. 119294
Permit No. 77145
Basin 153

**PRINT OR TYPE ONLY
DO NOT WRITE ON BACK**

*Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340*

NOTICE OF INTENT NO. 70172

1 OWNER J&T FARMS, LLC.
MAILING ADDRESS HC 62 BOX 62143 EUREKA, NEVADA
89316

ADDRESS AT WELL LOCATION DIAMOND VALLEY
Subdivision Name: _____ County: Eureka

2 LOCATION SW 1/4 NW 1/4 Sec 5 T 21N N/S R 54 E
PERMIT/WAIVER No. 77145
Issued by Water Resources Parcel No.

Latitude 39° 43.214 N UTM E NAD 27
Longitude 115° 55.327 W N NAD 83/WGS 84

3 TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

Is this well being plugged because a replacement well was drilled? YES
If yes, what is replacement well NOI? 70171
Is there an existing well log? YES
If yes, what is NDWR well log #? 72097

4 EXISTING WELL CONSTRUCTION
Depth Drilled 339' Feet Depth Cased 339' Feet

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why: _____

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16"		.250"	0'	299'
10 3/4"		.250"	299'	339'

Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no

Existing Perforations:

Type of perforation	Size of perforation	From	To
LOUVERED	1/8"	120'	160'
		215'	285'
		299'	339'

Additional Perforations:

Type of perforator used:	From	To	Number of perfs per linear foot
HOLTE AIR PERFORATOR	50'	120'	6 Rows
	160'	215'	6 Rows

5 WATER LEVEL
Static water level 64' feet below land surface
Artesian flow NO G.P.M. 0 P.S.I.
Water temperature COOL °F Quality _____

WELL PLUGGING MATERIALS

From	To	Material Used	Method
0'	20'	NEAT CEMENT	<input checked="" type="checkbox"/> Pumped <input type="checkbox"/> Poured
20'	339'	BENTONITE GROUT	<input checked="" type="checkbox"/> Pumped <input type="checkbox"/> Poured

6 Additional Notes or Comments
THE WELL COULD NOT BE PERFORATED PAST 215' BECAUSE THE WELL WAS COLAPSED AT THIS POINT.
plugs well log 72097
119294
39.720301°N
115.921026°W
STATE ENGINEERS OFFICE
2013 JUL 29 PM 12:21

Neat Cement Fluid Weight 15 LBS lbs/gal
Bentonite Grout 30% % bentonite
Date Started 7/12/2013
Date Completed 7/13/2013

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Hydro Resources - West, Inc. Contractor
Address 4975 W. Winnemucca Blvd. Contractor
Winnemucca, NV 89445
Nevada contractor's license number issued by the State Contractor's Board 56797
Nevada driller's license number issued by the Division of Water Resources, the on-site driller # 2483
Signed Michelle Strother By driller performing actual drilling on site or contractor
Date 7/25/13