STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 118811
Permit No.
Basin 212

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form it its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 37129

1. OWNER Dewey Strip Holdings L.L.C.
MAILING ADDRESS 9440 W. Sahara Ave. #240
Las Vegas Nv. 89117-8821

ADDRESS AT WELL LOCATION 4207 S. Las Vegas Blvd.
Las Vegas Nv. 89119

2. LOCATION SW ¼ SW ¼ Sec 28 T 21S N/S R 61 E
PERMIT/WAIVER No. 162-28-401-001
Issued by Water Resources Parcel No.

Latitude 36.089470
Longitude -115.172221
UTM E N
☐ NAD 27 ☑ NAD 83/WGS 84
Subdivision Name: *County:* Clark

3. WORKED PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other...

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☑ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☑ Other... auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Asphalt		0	.3	0
Type 2		.3	.6	0
Gray Sand w/Gravel		.6	3	2
Caliche		3	7	4
Sandy Silt W/Gravel		7	8.5	2
Caliche		8.5	11	3
Silty Sand		11	13	2
Caliche		13	14.5	2
Silty Sand W/Gravel		14.5	20.5	6
Caliche		20.5	25	5
Sand W/Gravel		25	37	12
Caliche		37	39	2
Cemented Gravel		39	41	2
Caliche		41	43	2
Cemented Gravel		43	45	2
Caliche		45	46	1
Sandy Silt W/Gravel Clay		46	60	14
PO-2				
see attached drawing for well construction				

DCNR/DWR/SNBO RECEIVED DEC 04 2013

Date started 11-5- , 20 13
Date completed 11/5/2013 , 20 13

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 60 Feet Depth Cased 57 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
12.5 Inches	0 Feet	60 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
.5		304ss Tubing	.5	57

Perforations:
Type of perforation Maching Slotted
Size of perforation .5" ss Screen

From 57	feet to	54	feet
From 50	feet to	47	feet
From 38	feet to	35	feet
From 30	feet to	27	feet
From 20	feet to	23	feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 24'
Placement Method: ☐ Pumped ☑ Poured
Gravel Packed: ☑ Yes ☐ No
From -.5 feet to 18' feet

Seal Type:
☐ Neat Cement
☐ Cement Grout
☑ Concrete Grout

9. WATER LEVEL
Static water level 19' feet below land surface
Artesian flow G.P.M P.S.I
Water temperature cool °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Eagle Drilling
Contractor
Address 7150 Placid St. L.V., Nv. 89119
Contractor
Nevada contractor's license number issued by the *State Contractor's Board* 51266
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 2477-M
Signed
By driller performing actual drilling on site or contractor
Date Dec 5, 2013

(Rev. 06/10)

USE ADDITIONAL SHEETS IF NECESSARY

NAD 27 36.089498 -115.1713892