STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 119 106
Permit No.
Basin 103

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 65678

1. OWNER Newmont USA Limited
MAILING ADDRESS PO Box 1658, Battle Mtn. NV. 89820

ADDRESS AT WELL LOCATION 4 miles East of SR 341 + 6 mile Canyon intersection Golden Eagle Mine
Subdivision Name: County:

2. LOCATION NE ¼ NE ¼ Sec 26 T 17 N/S R 21 E
PERMIT/WAIVER No. Nev 60600034
Issued by Water Resources Parcel No.

Latitude 39.31683
Longitude -119.58567
UTM E N
☐ NAD 27 ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition ☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test ☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC ☐ Air ☒ Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
MW-2				
Brown Fill Chaygravel Sand	21'	0	23'	23
Brown Yellow Clayey gravel Sand (dbl)	21	23	30	7
Blue Gray Weathered Andesite	21	30	51.5	21.5

NAD27
39.316914°N
119.584660°W

RECEIVED 2014 JAN 23 AM 11:24 STATE ENGINEER'S OFFICE

Date started: December 11, 20 13
Date completed: December 11, 20 13

7. Water Level
Static water level: 21' feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: <85 °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

9. WELL CONSTRUCTION
Depth Drilled 51.5 Feet Depth Cased 51.5 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
8 Inches	0 Feet	51.5 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2"		Sch 40	+2.6"	51.5'

Perforations:
Type of perforation Factory Slot
Size of perforation .020
From 10 feet to 51.5 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No

☐ Neat Cement	to		☐ Pumped	☐ Poured
☒ Cement Grout	0 to 7		☐ Pumped	☒ Poured
☐ Concrete Grout	to		☐ Pumped	☐ Poured
☐ ≥30% Bentonite Grout	to		☐ Pumped	☐ Poured

Gravel Pack: ☒ Yes ☐ No 9 to 51.5 ☐ Pumped ☒ Poured
Type: 10/20 Silica Sand
Bentonite Chips: ☒ Yes ☐ No 7 to 9 ☐ Pumped ☒ Poured
Type: 3/8 Bentonite chips

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Haz-Tech Drilling, Inc. (Contractor)
Address PO Box 940 (Contractor)
Meridian, Id. 83680
Nevada contractor's license number issued by the State Contractor's Board 0038018
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M2246
Signed Jason Adams (By driller performing actual drilling on-site or contractor)
Date 1-6-14

USE ADDITIONAL SHEETS IF NECESSARY

(Rev. 05-08)

(NSPO 3-08)

(O) 627