STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 119575
Permit No.
Basin No. 106

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 67509
WELL NAME (If applicable):

1. OWNER/CLIENT NAME Chris McAviney
MAILING ADDRESS 35 Villa Real Dr
Yerington, Nv 89447

DETAILED ADDRESS AT WELL LOCATION 35 Villa Real Dr
Yerington, Nv 89447
Subdivision Name: County: Lyon

2. PLS LOCATION NE ¼ NW ¼ 35 Sec 14N N/S 23 E
PERMIT/WAIVER NO. 14-371-21
issued by Water Resources Current Parcel No

Latitude N39.04122 UTM E ☐ NAD 27
Longitude W 119.04513 UTM N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
(X) New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
(X) Domestic ☐ Irrigation ☐ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☒ Rotary ☐ RVC
☐ Air ☒ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
Sandy top soil			0	2
Coarse sand, gravel & small rock				
fill			2	58
Coarse sand, gravel & brown clay			58	82
Coarse sand & gravel			82	95
Coarse sand, gravel & brown clay			95	101
Brown clay & coarse sand			101	107
Brown clay, coarse sand & gravel			107	140
Coarse sand & gravel			140	165
Brown clay & gravel			165	180
Coarse sand & gravel		X	180	202
Brown clay and gravel			202	208
Coarse sand, gravel & brown clay				
stratas		X	208	219
Brown clay & small gravel			219	229
Brown clay stratas, coarse sand				
and gravel stratas		X	229	242
Adapter PVC/Steel				
6" X 12" X .280				

Date started: 24-Feb , 20 14
Date completed: 3-Mar , 20 14

7. WATER QUALITIES
Static water level: 100' 6" Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: Cold ° Fahrenheit
Water Quality: Good

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☒ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
Air Line	50	240" air line	3 hours

9. INSTRUCTION
Depth Drilled: ~~239.5~~ 242 Feet Depth Cased: ~~241~~ 239.5 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
11 1/2	Inches	0	Feet	55	Feet
9 7/8	Inches	55	Feet	~~239.5~~	Feet
	Inches		Feet	241	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	12.92	.188 X 20' adapt .280	+ 1.5	19.5
6 5/8	3.63	SDR 21 PVC .316	19.5	239.5

ANNULAR MATERIALS
Sanitary Seal (X) Yes ☐ No

☐ Neat Cement		to	☐ Pumped	☐ Poured
☐ Cement Grout		to	☐ Pumped	☐ Poured
☒ Concrete Grout	0	to 70	☐ Pumped	(X) Poured
☐ Bentonite Chips		to	☐ Pumped	☐ Poured
☒ Gravel Pack [> 0.2 in.]	70	to 239.5	☐ Pumped	(X) Poured
☐ Sand Pack [< 0.2 in.]		to	☐ Pumped	☐ Poured
☐ Other, explain:		to	☐ Pumped	☐ Poured

PERFORATIONS:
Type of perforation: .032 X 6 Rows 1/4" spacing factory scree.
Size of perforation: 0.32

From 199.5	Feet	To 239.5	Feet
From	Feet	To	Feet
From	Feet	To	Feet
From	Feet	To	Feet
From	Feet	To	Feet

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name Ogden Drilling (Contractor)
Address 152 N Bybee Ln Yerington, Nv 89447 (Contractor)

Nevada contractor's license number as issued by the State Contractor's Board: 57011
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller): 634

Signed: Larry Ogden Sr (By driller performing actual drilling on site or contractor)
Date: 3-14-14

(Rev. 12-13) USE ADDITIONAL SHEETS IF NECESSARY pg. of pg.