

**STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT**

OFFICE USE ONLY
Log No. 119793
Permit No. 43833
Basin 105

**PRINT OR TYPE ONLY
DO NOT WRITE ON BACK**

*Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340*

NOTICE OF INTENT NO. 69883

1 OWNER Park Ranch ADDRESS AT WELL LOCATION 1/2 mile east of Heybourne Lane and
MAILING ADDRESS 1300 Buckeye Road 1/2 mile north of Buckeye Rd. near Minden, NV.
Minden, NV. 89423 Subdivision Name: _____ County: Douglas

2 LOCATION NE 1/4 NE 1/4 Sec 29 T 13N N/S R 20 E Latitude 38d 58.112 N UTM E _____ NAD 27
PERMIT/WAIVER No. 43833 Longitude 119d 45.307 W N _____ NAD 83/WGS 84
Issued by Water Resources Parcel No.

3 TYPE OF WELL Is this well being plugged because a Is there an existing well log? no
 Domestic Irrigation Test replacement well was drilled? n/a
 Municipal/Industrial Monitor Stock If yes, what is replacement well NOI? _____ If yes, what is NDWR well log #? _____

4 EXISTING WELL CONSTRUCTION
Depth Drilled 220 Feet Depth Cased 220 Feet
EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>18</u>		<u>.250</u>	<u>0</u>	<u>220</u>

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why: _____
Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no
If casing was left in place, please show where additional perforations were made: _____
Additional Perforations: _____

Existing Perforations:
Type of perforation n/a
Size of perforation n/a

From	feet to	feet

Type of perforator used: Mills Knife

From	feet to	feet	Number of perfs per linear foot
<u>100</u>	<u>surface</u>	<u> </u>	<u>6</u>

5 WATER LEVEL
Static water level 7.9' feet below land surface
Artesian flow _____ G.P.M. _____ P.S.I.
Water temperature _____ °F Quality _____

8 WELL PLUGGING MATERIALS

From	feet to	feet	Material Used	<input type="checkbox"/> Pumped	<input type="checkbox"/> Poured
<u>220</u>	<u>surface</u>	<u> </u>	<u>neat cement</u>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>
				<input type="checkbox"/>	<input type="checkbox"/>

6 Additional Notes or Comments

Removed 65' of 8" turbine pump from well. Measured well depth at 202'. Installed sand bucket and bailed to a hard bottom at 220'. Installed Mills Knife and perforated well from 100' back to surface, cutting 6 rows per foot. Removed Mills Knife and installed 215' of 2" tremmie pipe. The following day, we pumped in 16 yards of neat cement from the bottom of the well to the surface.

Neat Cement Fluid Weight 14.5 lbs/gal
Bentonite Grout _____ % bentonite
Date Started 11/26/2013
Date Completed 11/27/2013

2013 DEC - 6 AM 11:41
STATE ENGINEERS OFFICE
plugs unknown well log
NAD 27
38.96512 N
119.754106 W

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Carson Pump, LLC Contractor
Address P.O. Box 20159 Contractor
Carson City, NV. 89721
Nevada contractor's license number issued by the State Contractor's Board 39920A
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2265
Signed Joe Carter By driller performing actual drilling on site or contractor
Date 12/4/2013