

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. <u>12210</u>
Rec. <u>19</u>
Well No. _____
Permit No. _____

Do not fill in

Owner George or Maurice Uyull Driller W.L. McDonald

Address Rive rhelle Trailer Park; Verdi, NV Address 1955 18th St.; Sparks Lic. No. 493

Location of well: 1/4 NE 1/4 Sec. 15, T. 20 N, R. 19 E, in Washoe County  
or PONTIAC DRIVE

Water will be used for domestic purposes Total depth of well 100'

Size of drilled hole 8" Weight of casing per linear foot 11 lbs.

Thickness of casing .188 wall Temp. of water cold

Diameter and length of casing 65/800 X 20' lengths  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 47'

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well 4-3-72 (8AM) Date of completion of well 4-3-72 (11AM)

Type of well rig Ingersol Rand T-4 Drillmaster

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	3	3	Loamy topsoil	
3	5	2	Yellow sandy clay	
5	10	5	Fine to coarse silty yellow sand	Chief aquifer (water-bearing formation) from <u>75</u> to <u>85</u> ft.
10	49	39	Same as above w/ occasional clay lens. Formation changes from yellow to green to grey in color. Approx. 5% silt.	Other aquifers _____
49	58	9	Fine grey silty sand-5% silt	
58	70	12	Fine to coarse silty sand w/ some clay lenses & 1% rounded gravels to 3/8" diam.	
70	75	5	Clean coarse sand-damp	
75	100	25	Fine to coarse sand w/ rounded gravels to 1 1/2" diam. Water bearing 75-85.	First water at <u>75</u> feet.
				Casing perforated from <u>75</u> to <u>100</u> ft.
				Size of perforations <u>1/8" X 4"</u>



EXHIBIT "A"

A portion of the Northeast Quarter of the Northeast Quarter of Section 15, Township 20 North, Range 19 East, M.D.B.&M., being more particularly described as follows:

Commencing at the Northeast corner of said Section 15; thence South  $88^{\circ}44'30''$  West a distance of 975.62 feet; thence South  $02^{\circ}39'48''$  East a distance of 948.01 feet to the point of beginning; thence continuing South  $02^{\circ}39'48''$  East a distance of 136.04 feet; thence South  $88^{\circ}20'12''$  West a distance of 345.20 feet; thence North  $02^{\circ}39'48''$  West a distance of 136.04 feet; thence North  $87^{\circ}20'12''$  East a distance of 345.20 feet to the point of beginning.

RESERVING THEREBY a 10 foot wide easement along all side and rear property lines for drainage and utility purposes.

SUBJECT TO an easement for roadway purposes over the East 25 feet thereof.

TOGETHER WITH a non-exclusive easement for ingress and egress over a 50 foot wide strip of land the centerline being described as follows:

Commencing at the Northeast corner of said Section 15, thence South  $88^{\circ}44'30''$  West a distance of 975.62 feet to the point of beginning of said centerline; thence South  $02^{\circ}39'48''$  East a distance of 1361.74 feet to the point of ending.

218463