STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 12081
Permit No.
Basin No. 212

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 38102
WELL NAME *(if applicable)*: MW-2

1. OWNER/CLIENT NAME Whitton Corporation % Bank Las Vega
MAILING ADDRESS 1700 W. Horizon Ridge Pkwy#107
Henderson,NV 89012

DETAILED ADDRESS AT WELL LOCATION 3950 E. Sunset Rd-Paradise
Subdivision Name: *County:* Clark

2. PLS LOCATION SW ¼ SE ¼ 31 Sec 21S N/S 62 E
PERMIT/WAIVER NO. MO-2995 *Issued by Water Resources* 161-31-813-006 *Current Parcel No.*

Latitude 36 04'18.81"N UTM E ☐ NAD 27
Longitude 115 05'14.75"W UTM N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☒ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☒ Auger ☐ Rotary ☐ RVC
☐ Air ☐ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To	Thick-ness
Fill			0	2	2
Sandy Silt			2	12	10
Clayey Sand			12	20	8

CONRD/WRSNRC
RECEIVED
MAY 9 0 2014

Date started: 8-May , 20 2014
Date completed: 8-May , 20 2014

7. *WATER QUALITIES*
Static water level: 10 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: ° Fahrenheit
Water Quality:

8. WELL TEST DATA
Test Method: ☒ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
		.5

9. *WELL CONSTRUCTION*
Depth Drilled: 20 Feet Depth Cased: 20 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
8	Inches	0	Feet	20	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375		Sch 40	0	20

PERFORATIONS:
Type of perforation: Factory Slotted
Size of perforation: 0.02
From 10 Feet To 20 Feet
From Feet To Feet
From Feet To Feet

ANNULAR MATERIALS

☐ Sanitary Seal		to		
☐ Neat Cement		to	☐ Pumped	☐ Poured
☐ Cement Grout		to	☐ Pumped	☐ Poured
☐ Concrete Grout		to	☐ Pumped	☐ Poured
☒ Bentonite Chips	6	to 8	☐ Pumped	☒ Poured
☐ Bentonite Grout		to	☐ Pumped	☐ Poured
☐ 15 % ☐ 20 % ☐ Other, explain:				
☒ Gravel Pack [> 0.2 in.]	8	to 20	☐ Pumped	☒ Poured
☐ Sand Pack [< 0.2 in.]		to	☐ Pumped	☐ Poured
☐ Other, explain:		to	☐ Pumped	☐ Poured

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name Cascade Drilling L.P. *Contractor*
Address 4590 Copper Sage St., Las Vegas, NV 89115 *Contractor*
Nevada contractor's license number as issued by the *State Contractor's Board:* C23-0073966
Nevada well driller's license number as issued by the *Nevada Division of Water Resources (on-site driller)* 2381
Signed: *By driller performing actual drilling on site or contractor*
Date:

(Rev. 05-12) **USE ADDITIONAL SHEETS IF NECESSARY**

36.0719177
-115.0866012
NAD 27