STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 120643
Permit No.
Basin No. 090

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 71807
WELL NAME *(If applicable)*: MW-1

1. OWNER/CLIENT NAME Woodstock Development, Inc.
MAILING ADDRESS 330 Primrose Road Suite 203
Burlingame, CA 94010

DETAILED ADDRESS AT WELL LOCATION Facility ID: D-001019
Near 874 Ophir Peak Rd & Rubicon Peak Lane Incline Village, NV
Subdivision Name: *County:* Washoe

2. PLS LOCATION SW ¼ SW ¼ 15 Sec 16 N/S 18 E
PERMIT/WAIVER NO. Washoe County ROW
Issued by Water Resources *Current Parcel No.*

Latitude 39°14'41.74" UTM E ☐ NAD 27
Longitude 119°57'17.54" UTM N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☒ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☐ Rotary ☐ RVC
☒ Air ☐ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To	Thick-ness
Cobbles and Sand,			0		
Fine, Brown				70	70
Sand, coarse, weathered			70	81	11

RECEIVED 2014 AUG 29 AM 11:30 STATE ENGINEERS OFFICE

Nad 27
39.245020N
119.953850W

Date started: 29-Jul , 20 14
Date completed: 31-Jul , 20 14

9. WELL CONSTRUCTION
Depth Drilled: 81 Feet Depth Cased: 80 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
7	Inches	0	Feet	55	Feet
6	Inches	55	Feet	81	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2		Sch 40	0	80

PERFORATIONS:
Type of perforation: Slot
Size of perforation: 0.02
From 60 Feet To 80 Feet
From Feet To Feet
From Feet To Feet

ANNULAR MATERIALS

☒ Sanitary Seal	0 to 1.5			
☒ Neat Cement	1.5 to 53	☒ Pumped	☐ Poured	
☐ Cement Grout	to	☐ Pumped	☐ Poured	
☐ Concrete Grout	to	☐ Pumped	☐ Poured	
☒ Bentonite Chips	53 to 57	☐ Pumped	☒ Poured	
☐ Bentonite Grout	to	☐ Pumped	☐ Poured	
☐ 15 % ☐ 20 % ☐ Other, explain:				
☐ Gravel Pack [> 0.2 in.]	to	☐ Pumped	☐ Poured	
☒ Sand Pack [< 0.2 in.]	57 to 81	☐ Pumped	☒ Poured	
☐ Other, explain:	to	☐ Pumped	☐ Poured	

7. WATER QUALITIES
Static water level: 70 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: ° Fahrenheit
Water Quality:

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name Cascade Drilling, L.P.
Contractor
Address 3000 Duluth St West Sacramento, CA 95691
Contractor

Nevada contractor's license number as issued by the *State Contractor's Board:* 73966
Nevada well driller's license number as issued by the *Nevada Division of Water Resources (on-site driller):* 1991
Signed: *By driller performing actual drilling on site or contractor*
Date: 8/25/14

(Rev. 08-12)
USE ADDITIONAL SHEETS IF NECESSARY