

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S REPORT

OFFICE USE ONLY  
Log No. 120839  
Permit No. \_\_\_\_\_  
Basin 212

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 36839

1. OWNER Kady Corp.  
MAILING ADDRESS 9510 Pathway St. Suite B  
Santee, CA 92071

ADDRESS AT WELL LOCATION 1929 N. Las Vegas Blvd.  
N. Las Vegas, NV. 89030  
Subdivision Name: \_\_\_\_\_ County: Clark

2. LOCATION NW 1/4 SW 1/4 Sec 23 T 20 N R 61 E  
PERMIT/WAIVER No. 139-23-310-017  
Issued by Water Resources Parcel No. \_\_\_\_\_

Latitude N 36° 11' 43.95" UTM E  NAD 27  
Longitude W 115° 07' 46.69" N  NAD 83/WGS 84  
Client Well MW-1

3. WORKED PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Other

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other HSA

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
<u>FILL SAND &amp; GRAVEL</u>		<u>0</u>	<u>4</u>	
<u>SILTY SAND</u>		<u>4</u>	<u>5 1/2</u>	<u>1 1/2</u>
<u>CALICHE</u>		<u>5 1/2</u>	<u>6 1/2</u>	<u>1</u>
<u>SANDY CLAY</u>		<u>6 1/2</u>	<u>10</u>	<u>3 1/2</u>
<u>SILTY SAND</u>	<u>yes</u>	<u>10</u>	<u>12</u>	<u>2</u>
<u>SILTY CLAY</u>		<u>12</u>	<u>25</u>	<u>13</u>

9. WELL CONSTRUCTION

Depth Drilled 25 Feet Depth Cased 25 Feet

HOLE DIAMETER (BIT SIZE)

From	To
<u>8</u> Inches	<u>0</u> Feet <u>25</u> Feet
_____ Inches	_____ Feet _____ Feet
_____ Inches	_____ Feet _____ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>2" sch 40 PVC</u>		<u>ASTM 480</u>	<u>0</u>	<u>25</u>

Date started: 4/28, 20 14  
Date completed: 4/29, 20 14

Perforations:  
Type of perforation Factory Slots  
Size of perforation .820"  
From 10 feet to 25 feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Annular Seal:  Yes  No

Neat Cement \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 Cement Grout \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 Concrete Grout 0 to 2  Pumped  Poured  
 ≥30% Bentonite Grout \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured

Gravel Pack:  Yes  No 8 to 25  Pumped  Poured  
Type: #3/16 Matching Silica

Bentonite Chips:  Yes  No 2 to 8  Pumped  Poured  
Type: Hydrated 3/8 Bentonite Hole Plug

7. Water Level  
Static water level: 11 feet below land surface  
Artesian Flow: \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water Temperature: \_\_\_\_\_ °F  
Quality: \_\_\_\_\_

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name Elite Drilling Inc. Contractor  
Address 4255 W. Post Rd. Contractor  
Las Vegas, NV. 89118  
Nevada contractor's license number \_\_\_\_\_  
issued by the State Contractor's Board 054931  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1944  
Signed Thomas M. Beall  
By driller performing actual drilling on-site or contractor  
Date 5/8/14

8. WELL TEST DATA

TEST METHOD:  Bailer  Pump  Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<u>N/A</u>		

(Rev. 05-05)

USE ADDITIONAL SHEETS IF NECESSARY

(NSPO 3-08)

36,195,575  
-115,128,013

NAD  
27