STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 121368
Permit No.
Basin No. 212

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 38112
WELL NAME (If applicable): AS-2

1. OWNER/CLIENT NAME CK 3285 S. Nellis Blvd LLC%L
MAILING ADDRESS 10300 W. Charleston Blvd#13-156
Las Vegas, NV 89135

DETAILED ADDRESS AT WELL LOCATION 3285 S. Nellis Blvd
Sunrise Manor
Subdivision Name: County: Clark

2. PLS LOCATION SE ¼ SE ¼ 8 Sec 21S N/S 62 E
PERMIT/WAIVER NO. 161-08-810-062
Issued by Water Resources Current Parcel No.

Latitude 36 7'47.46"N UTM E ☐ NAD 27
Longitude 115 3'57.29" UTM N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☒ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☒ Auger ☐ Rotary ☐ RVC
☐ Air ☐ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To	Thickness
Fill			0	1	1
Silty Sand			1	9	8
Sand			9	13	4
Sandy Silt			13	30	17

NR/DWR/SNBC
RECEIVED
JUL 18 2014

Date started: 10-Jun , 20 14
Date completed: 10-Jun , 20 14

9. WELL CONSTRUCTION
Depth Drilled: 30 Feet Depth Cased: 30 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
8	Inches	0	Feet	30	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375		Sch 40	0	30

PERFORATIONS:
Type of perforation: Factory Slotted
Size of perforation: 0.02
From 28 Feet To 30 Feet
From Feet To Feet
From Feet To Feet

ANNULAR MATERIALS

☐ Sanitary Seal		to			
☐ Neat Cement		to		☐ Pumped	☐ Poured
☒ Cement Grout	1	to	10	☒ Pumped	☐ Poured
☐ Concrete Grout		to		☐ Pumped	☐ Poured
☒ Bentonite Chips	10	to	26	☐ Pumped	☒ Poured
☐ Bentonite Grout		to		☐ Pumped	☐ Poured
☐ 15 % ☐ 20 % ☐ Other, explain:					
☒ Gravel Pack [> 0.2 in.]	26	to	30	☐ Pumped	☒ Poured
☐ Sand Pack [< 0.2 in.]		to		☐ Pumped	☐ Poured
☐ Other, explain:		to		☐ Pumped	☐ Poured

7. WATER QUALITIES
Static water level: 15 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: ° Fahrenheit
Water Quality:

8. WELL TEST DATA
Test Method: ☒ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
		.5

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name Cascade Drilling L.P.
Contractor
Address 4590 Copper Sage St., Las Vegas, NV 89115
Contractor
Nevada contractor's license number as issued by the State Contractor's Board: C23-0073966
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller): 2381
Signed: By driller performing actual drilling on site or contractor
Date: 7-18-14

(Rev. 08-12)

USE ADDITIONAL SHEETS IF NECESSARY

36. 1298 22
115. 06 58 20