STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 121378
Permit No.
Basin No.

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 37802
WELL NAME *(if applicable)*: MW-14

1. OWNER/CLIENT NAME 7-Eleven / Jose Rios
MAILING ADDRESS PO Box 711 Dallas TX 75221

DETAILED ADDRESS AT WELL LOCATION 5110 S Maryland Parkway
Las Vegas, NV 89119
Subdivision Name: *County:* Clark

2. PLS LOCATION SE ¼ NW ¼ 4 Sec 21 N/S 61 E
PERMIT/WAIVER NO. 162-26-210-013
Issued by Water Resources *Current Parcel No.*

Latitude 36* 05' 49.35"'N UTM E ☒ NAD 27
Longitude 115* 08' 10.73"W UTM N ☐ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☒ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☒ Auger ☐ Rotary ☐ RVC
☐ Air ☐ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
Asphalt			0	4"
TYPE II Base			4"	10"
Gravel Silty W/ Cobbles			10"	5'
Gravelly silt, very stiff,moist			5	
subangular gravels				7'
Caliche			7'	14
Gravelly silt, very stiff,moist			13.5	
subangular gravels				22'
Caliche			22'	26'

Date started: 31-Oct , 20 14
Date completed: 31-Oct , 20 14

DCNR/DWR/SNBC
RECEIVED
NOV 17 2014

9. *INSTRUCTION*
Depth Drilled: 26 Feet Depth Cased: 25 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 1/4"	Inches	0	Feet	26	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4.500	2.01	0.237	0	25

ANNULAR MATERIALS
Sanitary Seal ☒ Yes ☐ No

☒ Neat Cement	0	to 2	☐ Pumped	☒ Poured
☐ Cement Grout		to	☐ Pumped	☐ Poured
☐ Concrete Grout		to	☐ Pumped	☐ Poured
☒ Bentonite Chips	6	to 8	☐ Pumped	☒ Poured
☐ Gravel Pack [> 0.2 in.]		to	☐ Pumped	☐ Poured
☒ Sand Pack [< 0.2 in.]	8	to 25	☐ Pumped	☒ Poured
☒ Other, explain: Bentonite Grout	2	to 6	☐ Pumped	☒ Poured

PERFORATIONS:
Type of perforation: Factory
Size of perforation: 0.02

From	Feet	To	Feet
10		25	

7. *WATER QUALITIES*
Static water level: 16' Feet below land surface
Artesian Flow: NA G.P.M. NA P.S.I.
Water Temperature: NA ° Fahrenheit
Water Quality: Clear

8. WELL TEST DATA
Test Method: ☒ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name National EWP
Contractor
Address 5241 Schirlls Street, Las Vegas, NV 89118
Contractor

Nevada contractor's license number as issued by the *State Contractor's Board:* 00735355
Nevada well driller's license number as issued by the *Nevada Division of Water Resources (on-site driller):* 2512
Signed: Bob [illegible]
By driller performing actual drilling on site or contractor
Date: 11/14/14

(Rev. 12-13) **USE ADDITIONAL SHEETS IF NECESSARY** pg. of pg.

36.09704167
-115.13631339
NAD 27