Plugging

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 121491
Permit No. 70841
Basin 117

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

Original Log No. — 14663

NOTICE OF INTENT NO. 32997

1. OWNER White Mtn. Ranch
MAILING ADDRESS 144 West Brigham Rd. No 5 St. George UT, 89790

ADDRESS AT WELL LOCATION 2 Miles North of Dyer NV. on Hwy 264
Subdivision Name: County: Esmeralda

2. LOCATION SE ¼ SE ¼ Sec 9 T 3 N/S R 35 E
PERMIT/WAIVER No. 70841 Issued by Water Resources Parcel No.

Latitude N 37° 41.221 UTM E ☐ NAD 27
Longitude W 118° 05.325 N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Other Abandon

4. PROPOSED USE
☐ Domestic ☒ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
cleaned out to 210'.				
Preforated Casing with				
6 Ros, pref from 0 to 57'				
feet then pumped				
24% Benonite Groute				
Back to 20' feet from				
Surface then pumped				
20' feet Neat Cement				
to Surface				

DCNR/DWR/SNBC RECEIVED
OCT 01 2014

Date started: Sept 18th, 20 14
Date completed: Sept 19th, 20 14

7. Water Level
Static water level: 180' feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

9. WELL CONSTRUCTION
Depth Drilled 210' Feet Depth Cased 197' Feet

HOLE DIAMETER (BIT SIZE) By old Log.

	From	To
Inches	Feet	Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
14"	.188	.188	T1	197

Perforations:
Type of perforation Holt Air Pref 1/4"
Size of perforation 6 Rows
From 0 feet to 57 ft feet
From feet to feet
From feet to feet
From 3/16" Torch Cut 57 feet to 197 feet
From feet to feet

Annular Seal: ☐ Yes ☒ No
☒ Neat Cement 0 to 20 ☐ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☒ 24 Bentonite Grout 20 to 210 ☒ Pumped ☐ Poured
Gravel Pack: ☐ Yes ☐ No to ☐ Pumped ☐ Poured
Type:
Bentonite Chips: ☐ Yes ☐ No to ☐ Pumped ☐ Poured
Type:

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Teach Drilling Inc
Contractor
Address PO Box 598
Contractor
Silver Springs, NV 89429
Nevada contractor's license number issued by the State Contractor's Board 31841
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1876
Signed Nathinal R. Pearl
By driller performing actual drilling on-site or contractor
Date Sept 24, 2014

RECEIVED 2014 DEC 22 AM 11:41 STATE ENGINEER OFFICE

(Rev 05-06)

USE ADDITIONAL SHEETS IF NECESSARY

NAD27
37.6872141
-118.0877865

(NSPO 3-08) (O) 627