STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 121597
Permit No.
Basin No. 105

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 70828
WELL NAME (If applicable):

1. OWNER/CLIENT NAME Phil Edonson
MAILING ADDRESS 864 Baymore Huntington Beach CA 92646
DETAILED ADDRESS AT WELL LOCATION 1148 Autumn Hills Douglas
Subdivision Name: County:

2. PLS LOCATION SE ¼ NE ¼ 09 Sec 12 N/S 19 E
PERMIT/WAIVER NO. 1219.09.001030
Issued by Water Resources Current Parcel No.
Latitude 38°55.227 UTM E ☐ NAD 27
Longitude 119°50.768 UTM N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☒ Rotary ☐ RVC
☐ Air ☒ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To	Thickness
Dirt Cobbles			0	22	22
Brown clay			22	60	38
SAND - DG			60	155	95
Frac Gravel		X	155	300	145
NAD27					
38.920543°N					
119.845121°W					

Date started: 8-11, 20 14
Date completed: 8-14, 20 14

9. WELL CONSTRUCTION
Depth Drilled: 300 Feet Depth Cased: 300 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
14	Inches	0	Feet	20	Feet
11	Inches	20	Feet	300	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	.16	.188	+3	300'

PERFORATIONS:
Type of perforation: Factory
Size of perforation: 3/32 X 3
From 160 Feet To 180 Feet
From 200/240 Feet To 240/300 Feet
From Feet To Feet

ANNULAR MATERIALS
☒ Sanitary Seal to
☐ Neat Cement to ☐ Pumped ☐ Poured
☒ Cement Grout 0 to 103 ☒ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ Bentonite Chips to ☐ Pumped ☐ Poured
☐ Bentonite Grout to ☐ Pumped ☐ Poured
☐ 15 % ☐ 20 % ☐ Other, explain:
☐ Gravel Pack [> 0.2 in.] to ☐ Pumped ☐ Poured
☐ Sand Pack [< 0.2 in.] to ☐ Pumped ☐ Poured
☐ Other, explain: to ☐ Pumped ☐ Poured

7. WATER QUALITIES
Static water level: 135 Feet below land surface
Artesian Flow: NA G.P.M. NA P.S.I.
Water Temperature: Cold ° Fahrenheit
Water Quality: clear

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
15 GPM		5

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name BLAIN DRILLING & PUMP CO INC.
Contractor
Address P.O. Box 1255
Carson City, NV 89702
Contractor
Nevada contractor's license number as issued by the State Contractor's Board: 46498A
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller): 2134
Signed: [signature]
By driller performing actual drilling on site or contractor
Date: 9-12-14

RECEIVED 2014 JAN -5 AM 11:16 STATE ENGINEER'S OFFICE

(Rev. 08-12)
USE ADDITIONAL SHEETS IF NECESSARY
(NSPO Rev 11-12)
(O) 627