

**STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT**

OFFICE USE ONLY
Log No. 121657
Permit No. _____
Basin No. 047

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 71683
WELL NAME (if applicable) _____

1. OWNER/CLIENT NAME Bald Mountain / Barrick
MAILING ADDRESS PO Box 2706
Elko NV 89803

DETAILED ADDRESS AT WELL LOCATION Bald Mountain -State Rte 892
Subdivision Name _____ County Elko

2. PLS LOCATION NW 1/4 SE 1/4 14 Sec 24 N1S 56 E
PERMIT/WAIVER NO. _____
Issued by Water Resources Current Parcel No.

Latitude 618826 NAD 27
Longitude 4423365 NAD 83-WGS 84

3. WORKED PERFORMED
 New Well Deepen. Orig WLM# _____
 Replacement. Original well log # _____
 Recondition. Original well log # _____

4. PROPOSED USE
 Domestic Irrigation Monitor
 Mining / Dewater Com / Ind Stock
 Test / Other Mun / QM Rec

5. WELL TYPE
 Auger Rotary RVC
 Air Mud Sonic
 Other

LITHOLOGIC LOG				
Material Encountered	Last Cnc	Water Strata	From	To
Silty Sand with gravel (SM/GM)			0	
Light Brown, Dry				17
Sand gravel with few cobbles			17	
Brown to Grey, Dry				26
No Sdample Cobbles			26	38
Sand gravel with few cobbles			38	
Brown to Grey, Dry				42
Silty Sand with gravel (SM/GM)			42	
Brown to Light Brown, Dry				44
Silty Sand with gravel (SM/GM)			44	
Trace of clay, Brown to Light Brwn				
Dry				54
Silty Sand Gravel with Few			54	
Cobbles and a trace of clay, Dry				61

9. INSTRUCTION
Depth Drilled: 61 Feet Depth Cased: 61 Feet

HOLE DIAMETER (BIT SIZE)				
	From	To		
	0	61	8.25	Feet
				Feet
				Feet

CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375	0.68	0.154	0	60

ANNULAR MATERIALS
Sanitary Seal Yes No
 Neet Cement 0 to 39 Pumped Poured
 Cement Grout _____ to _____ Pumped Poured
 Concrete Grout _____ to _____ Pumped Poured
 Bentonite Chips 39 to 42 Pumped Poured
 Gravel Pack [> 0.2 in.] _____ to _____ Pumped Poured
 Sand Pack [< 0.2 in.] 42 to 60 Pumped Poured
 Other, explain: 60 to 61 Pumped Poured
Backfilled 61 to 60 coated Bentonite Pellets

Date started: 10-Sep , 20 14
Date completed: 10-Sep , 20 14

PERFORATIONS:
Type of perforation: Factory
Size of perforation: 0.02
From 45 Feet To 60 Feet
From _____ Feet To _____ Feet
From _____ Feet To _____ Feet
From _____ Feet To _____ Feet

7. WATER QUALITIES
Static water level: NA Feet below land surface
Artesian Flow: NA G.P.M. P.S.I.
Water Temperature: NA ° Fahrenheit
Water Quality: NA

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name National EWP Contractor
Address 5241 Schrills St. Las Vegas NV 89118 Contractor

8. WELL TEST DATA			
Test Method:	G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
<input type="checkbox"/> Beller <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			

Nevada contractor's license number as issued by the State Contractor's Board: 0075355
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller): 2057
Signed: [Signature]
Date: 11/20/15

RECEIVED
 2015 JAN 20 PM 2:04
 STATE ENGINEERS OFFICE