STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 121658
Permit No.
Basin No. 105

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 72971
WELL NAME (If applicable):

1. OWNER/CLIENT NAME CHRIS HENDRICKSEN
MAILING ADDRESS 965 RIVERVIEW DR
GARDNERVILLE, NV 89460

DETAILED ADDRESS AT WELL LOCATION 965 RIVERVIEW DR
GARDNERVILLE, NV 89460
Subdivision Name: County: Douglas

2. PLS LOCATION NW ¼ NE ¼ 15 Sec 12 N/S 20 E
PERMIT/WAIVER NO. DOM14-64 (Issued by Water Resources) 1220-15-510-011 (Current Parcel No.)

Latitude 38.909073*N UTM E
Longitude 119.720594*W UTM N
☐ NAD 27 ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☐ New Well ☒ Deepen: Orig WL# N/A
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☒ Rotary ☐ RVC
☐ Air ☒ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
OLD 6 5/8 WELL			0	95
OBSIDIAN SANDS			95	110
BROWN CLAY SEAM			110	118
SANDS AND GRAVELS			118	165
COURSE GRAVELS		XXX	165	220

NAD 27
38.909823°N
119.719585°W

Date started: 15-Jan, 20 2015
Date completed: 16-Jan, 20 2015

9. INSTRUCTION
Depth Drilled: 125 Feet Depth Cased: 125 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
6 1/8	Inches	95	Feet	220	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
5	3.96	.214	80	220

ANNULAR MATERIALS
Sanitary Seal X ☐ Yes ☐ No

☐ Neat Cement		to	☐ Pumped	☐ Poured
☐ Cement Grout	N/A	to	☐ Pumped	☐ Poured
☐ Concrete Grout		to	☐ Pumped	☐ Poured
☐ Bentonite Chips		to	☐ Pumped	☐ Poured
☒ Gravel Pack [> 0.2 in.]	N/A	to	☐ Pumped	☐ Poured
☐ Sand Pack [< 0.2 in.]		to	☐ Pumped	☐ Poured
☐ Other, explain:		to	☐ Pumped	☐ Poured

PERFORATIONS:
Type of perforation: FACTORY MILL SLOT
Size of perforation: 0.032

From	Feet	To	Feet
180	Feet	220	Feet
	Feet		Feet
	Feet		Feet
	Feet		Feet
	Feet		Feet

7. WATER QUALITIES
Static water level: 55 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: 49 ° Fahrenheit
Water Quality: GOOD

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
30	30	3 HOURS

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name CAPITAL CITY WELL DRILLING AND PUMP SERVICE INC. (Contractor)
Address 20 KIT KAT DRIVE CARSON CITY, NV 89706 (Contractor)
Nevada contractor's license number as issued by the State Contractor's Board: 0055548
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller): 4905
Signed: Michael L Hack (By driller performing actual drilling on site or supervisor)
Date: 1/20/2015

(Rev. 12-13) USE ADDITIONAL SHEETS IF NECESSARY pg. of pg.

Deepens Unknown Well log