STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 121902
Permit No.
Basin

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 36843

1. OWNER Sahara Las Vegas Corp.
MAILING ADDRESS 3221 S. Torry Pines
Las Vegas NV 89146

ADDRESS AT WELL LOCATION 2737 Paradise Rd
Las Vegas, NV 89109
Subdivision Name: County:

2. LOCATION SE ¼ NE ¼ Sec 9 T 21 N R 61 E
PERMIT/WAIVER No. MD-3001 Issued by Water Resources
162-09-602-005 Parcel No.

Latitude 36.14019°
Longitude -115.15518

UTM E N
☐ NAD 27
☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
FILL CLAYEY SAND		0	4	4
CLAYEY SAND		4	11	7
SILTY CLAY	wet	11	19	8
CLAYEY GRAVEL	wet	19	25	6
SILTY CLAY		25	29	6
SILTY SAND	wet	29	35	6
CLAYEY SAND		35	39	4
SILTY SAND	wet	39	44	5
CLAYEY SAND		44	59	15
SANDY CLAY		59	64	5
CLAYEY SAND		64	69	5
SILTY CLAY		69	73	4
CLAYEY GRAVEL	wet	73	77	4
SILTY CLAY		77	80	3

DCNR/DWR/SNBO
RECEIVED
DEC 22 2014

Date started: 11/14, 20 014
Date completed: 11/14, 20 014

9. WELL CONSTRUCTION
Depth Drilled 80 Feet Depth Cased 80 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
6	Inches	0	Feet	80	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2" sch40 PVC			0	80

Perforations:
Type of perforation Factory Slots
Size of perforation .020
From 20 feet to 60 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☒ Concrete Grout 0 to 16 ☐ Pumped ☒ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ☒ Yes ☐ No 18 to 80 ☐ Pumped ☒ Poured
Type: #12 Silica Sand
Bentonite Chips: ☒ Yes ☐ No 16 to 18 ☐ Pumped ☒ Poured
Type: 3/8 Bentonite Hole Plug

7. Water Level
Static water level: 15 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
NA		

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Elite Drilling Inc (Contractor)
Address 4255 W. Post Rd. (Contractor)
Las Vegas, NV. 89118
Nevada contractor's license number issued by the State Contractor's Board 054931
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1944
Signed Thomas M. Beall (By driller performing actual drilling on-site or contractor)
Date 12/18/14

(Rev. 05-06)
USE ADDITIONAL SHEETS IF NECESSARY

36.140219 NAD 27
-115.1543467

(NSPO 3-08) (O) 627