STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 121904
Permit No.
Basin

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 36845

1. OWNER Sahara Las Vegas Corp
MAILING ADDRESS 3221 S. Torrey Pines
Las Vegas, NV. 89146

ADDRESS AT WELL LOCATION 2601 S. Las Vegas Blvd.
Las Vegas, NV. 89109
Subdivision Name: County: CLARK

2. LOCATION SE ¼ NE ¼ Sec 9 T 21 N/S R 61 E/W
PERMIT/WAIVER No. MO-3000 (Issued by Water Resources) 162-09-602-001 (Parcel No.)

Latitude 36.13895 Longitude -115.15877
UTM E N
☐ NAD 27 ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition ☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test ☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC ☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
FILL SANDY CLAY		0	2	2
CALICHE		2	3	1
CLAYEY SAND		2	18	16
SANDY CLAY	wet	18	24	6
SILTY CLAY		24	29	5
CLAYEY SAND		29	35	6
CALICHE		35	40	5
SANDY CLAY		40	44	4
SILTY SAND	wet	44	49	5
CALICHE		49	65	16
SANDY CLAY		65	70	5
CLAYEY SAND		70	75	5
SANDY CLAY		75	80	5

DCNR/DWR/SNBC RECEIVED DEC 22 2014

Date started: 11/19, 20 14
Date completed: 11/19, 20 14

7. Water Level
Static water level: 20 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
NA		

9. WELL CONSTRUCTION
Depth Drilled 80 Feet Depth Cased 80 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
6	Inches	0	Feet	80	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2" sch 40 PVC			20	80

Perforations:
Type of perforation Factory Slots
Size of perforation .020
From 20 feet to 80 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☒ Concrete Grout 0 to 16 ☐ Pumped ☒ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ☒ Yes ☐ No 18 to 80 ☐ Pumped ☒ Poured
Type: #12 Silica Sand
Bentonite Chips: ☒ Yes ☐ No 16 to 18 ☐ Pumped ☐ Poured
Type: 3/8

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Elite Drilling Inc. (Contractor)
Address 4255 W. Post Rd. (Contractor)
Las Vegas, NV. 89118
Nevada contractor's license number issued by the State Contractor's Board 054931
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1944
Signed Thomas N. Beall (By driller performing actual drilling on-site or contractor)
Date 12/18/14

(Rev. 06-08)
USE ADDITIONAL SHEETS IF NECESSARY

36.138979
-115.1579367
NAD 27

(NSPO 3-08)
(O) 627