STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 12949
Permit No.
Basin No. CU

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 72248
WELL NAME (If applicable): MW-6-R

1. OWNER/CLIENT NAME Veris Gold U.S.A. Inc. Mirinda Jones
MAILING ADDRESS HC 31 Box 78, Elko, NV 89801

DETAILED ADDRESS AT WELL LOCATION JERRIT CANYON MINE, IN THE MILL AREA
Subdivision Name. County: Elko

2. PLS LOCATION SE ¼ NW ¼ 33 Sec 41N N/S 54 E
PERMIT/WAIVER NO. M/O-1971
Issued by Water Resources Current Parcel No.

Latitude 41.40918 UTM E ☐ NAD 27
Longitude -115.903 UTM N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
[ ] New Well ☐ Deepen: Orig WL#
☒ Replacement: Original well log # unsure
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☒ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☒ Auger ☐ Rotary ☐ RVC
☐ Air ☐ Mud ☐ Sonic
☒ Other H.S.A.

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
fill, gravel		dry	0	2
tan sandy silt w/gravel layers			2	11
gravels w/sand, silty clay matrix			11	24
brown clay			24	29
cemented sandy gravels			28.5	47

Replaced Instrument tag
Nad 27
41.40918°N
115.903000°W

Date started: 7-Feb, 20 15
Date completed: 7-Feb, 20 15

7. WATER QUALITIES
Static water level: dry Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: na ° Fahrenheit
Water Quality: na

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)

9. INSTRUCTION
Depth Drilled: 47 Feet Depth Cased: 47 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10.5	Inches	0	Feet	47	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4"		sch 40	+2'	47

ANNULAR MATERIALS
Sanitary Seal ☒ Yes ☐ No

☐ Neat Cement	0	to 23	☒ Pumped	☐ Poured
☐ Cement Grout		to	☐ Pumped	☐ Poured
☐ Concrete Grout		to	☐ Pumped	☐ Poured
☒ Bentonite Chips	23	to 25	☐ Pumped	☒ Poured
☐ Gravel Pack [> 0.2 in.]		to	☐ Pumped	☐ Poured
☐ Sand Pack [< 0.2 in.]	25	to 47	☐ Pumped	☒ Poured
☐ Other, explain:		to	☐ Pumped	☐ Poured

PERFORATIONS:
Type of perforation: factory slot
Size of perforation: 0.01

From	Feet	To	Feet
27		47	

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name HAZ-TECH DRILLING INC. (Contractor)
Address P.O. BOX 940 MERIDIAN, ID. 83680 (Contractor)
Nevada contractor's license number as issued by the State Contractor's Board: 0038018
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller): M-2188
Signed: (By driller performing actual drilling on site or contractor)
Date: 2/16/2015

(Rev. 12-13) USE ADDITIONAL SHEETS IF NECESSARY pg. of pg.