STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 121970
Permit No.
Basin No.

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 38137
WELL NAME *(if applicable)*: MW-9

1. OWNER/CLIENT NAME Primm South Real Estate Company
MAILING ADDRESS 5420 Kietzke Ln#108
Reno, NV 89511-2063

DETAILED ADDRESS AT WELL LOCATION 100 W. Primm Blvd-clark county
Subdivision Name *County:* Clark

2. PLS LOCATION NE ¼ SW ¼ 8 Sec 27S N/S 59 E
PERMIT/WAIVER NO. MO-3013 *issued by Water Resources* 237-08-301-003 *Current Parcel No.*

Latitude 35°36'39.04"N UTM E ☐ NAD 27
Longitude 115°23'26.91"W UTM N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☒ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☒ Auger ☐ Rotary ☐ RVC
☐ Air ☐ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
Fill			0	2
Clayey Sand			2	20
Clayey Gravel			20	40
Silty Sand			40	60
Clayey Silt			60	80
Clayey Sand			80	98

DCNR/DWR/SNRE RECEIVED FEB 23 2015

Date started: 2-Feb 20 15
Date completed: 3-Feb 20 15

7. WATER QUALITIES
Static water level: 87 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: ° Fahrenheit
Water Quality:

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)

9. CONSTRUCTION
Depth Drilled: 98 Feet Depth Cased: 98 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
8 Inches		0 Feet	98 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375		Sch 80	0	98

ANNULAR MATERIALS
Sanitary Seal ☐ Yes ☐ No

☐ Neat Cement		to	☐ Pumped	☐ Poured
☒ Cement Grout	1	to 74	☒ Pumped	☐ Poured
☐ Concrete Grout		to	☐ Pumped	☐ Poured
☒ Bentonite Chips	74	to 76	☐ Pumped	☒ Poured
☒ Gravel Pack [> 0.2 in.]	76	to 98	☐ Pumped	☒ Poured
☐ Sand Pack [< 0.2 in.]		to	☐ Pumped	☐ Poured
☐ Other, explain:		to	☐ Pumped	☐ Poured

PERFORATIONS:
Type of perforation: Factory Slotted
Size of perforation: 0.01
From 78 Feet To 98 Feet
From Feet To Feet
From Feet To Feet
From Feet To Feet
From Feet To Feet

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name Cascade Drilling, L.P. *Contractor*
Address 4590 Copper Sage ST, Las Vegas, NV 89115 *Contractor*
Nevada contractor's license number as issued by the *State Contractor's Board*: 0073966
Nevada well driller's license number as issued by the *Nevada Division of Water Resources (on-site driller)*: 2381
Signed: *By driller performing actual drilling on site or contractor*
Date: 2-18-15

(Rev. 12-13) USE ADDITIONAL SHEETS IF NECESSARY pg. of pg.

35.6103623
-115.3899812
NAD 27