STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 121971
Permit No.
Basin No.

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 38138
WELL NAME (if applicable): MW-10

1. OWNER/CLIENT NAME: Primm South Real Estate Company
MAILING ADDRESS: 5420 Kietzke Ln#108
Reno, NV 89511-2063

DETAILED ADDRESS AT WELL LOCATION: 100 W. Primm Blvd-clark county
Subdivision Name: County: Clark

2. PLS LOCATION: NE ¼ SW ¼ 8 Sec 27S N/S 59 E
PERMIT/WAIVER NO.: MO-3013 (Issued by Water Resources) 237-08-301-002 (Current Parcel No.)

Latitude 35°36'34.69"N UTM E ☐ NAD 27
Longitude 115°23'34.99"W UTM N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☒ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☒ Auger ☐ Rotary ☐ RVC
☐ Air ☐ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
Fill			0	2
Clayey Sand			2	40
Sand			40	60
Sandy Gravel			60	80
Clayey Gravel			80	97

DCNR/DWR/SNB
RECEIVED
DCNR/DWR/SNB
RECEIVED
FEB 2 8 2015

Date started: 27-Jan, 20 15
Date completed: 28-Jan, 20 15

9. CONSTRUCTION
Depth Drilled: 97 Feet Depth Cased: 97 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
8	Inches	0	Feet	97	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375		Sch 80	0	97

ANNULAR MATERIALS
Sanitary Seal ☐ Yes ☐ No

☐ Neat Cement		to		☐ Pumped	☐ Poured
☒ Cement Grout	1	to	73	☒ Pumped	☐ Poured
☐ Concrete Grout		to		☐ Pumped	☐ Poured
☒ Bentonite Chips	73	to	75	☐ Pumped	☒ Poured
☒ Gravel Pack [> 0.2 in.]	75	to	97	☐ Pumped	☒ Poured
☐ Sand Pack [< 0.2 in.]		to		☐ Pumped	☐ Poured
☐ Other, explain:		to		☐ Pumped	☐ Poured

PERFORATIONS:
Type of perforation: Factory Slotted
Size of perforation: 0.01

From	Feet	To	Feet
77	Feet	97	Feet
	Feet		Feet
	Feet		Feet
	Feet		Feet
	Feet		Feet

7. WATER QUALITIES
Static water level: 87 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: ° Fahrenheit
Water Quality:

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name: Cascade Drilling, L.P. (Contractor)
Address: 4590 Copper Sage ST, Las Vegas, NV 89115 (Contractor)
Nevada contractor's license number as issued by the State Contractor's Board: 0073966
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller): 2381
Signed: (By driller performing actual drilling on site or contractor)
Date: 2-18-15

(Rev. 12-13) USE ADDITIONAL SHEETS IF NECESSARY pg. of pg.

35.6096541 NAD
-115.3922255 27