

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 122070
Permit No.
Basin 064

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 71257

1 OWNER NV ENERGY
MAILING ADDRESS 6226 W. SAHARA
LAS VEGAS NV

ADDRESS AT WELL LOCATION N. VALMY POWER
GENERATION PLANT, VALMY, NV
Subdivision Name: County: HUMBOLT

2 LOCATION SW 1/4 NW 1/4 Sec 28 T 35 S R 28 E
PERMIT/WAIVER No.

Latitude 40° 52' 56.49" UTM E
Longitude 117° 08' 41.35" N
 NAD 27
 NAD 83/WGS 84

3 TYPE OF WELL
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

Is this well being plugged because a replacement well was drilled?
If yes, what is replacement well NOI? 67309
Is there an existing well log?
If yes, what is NDWR well log #?

4 EXISTING WELL CONSTRUCTION
Depth Drilled 120 Feet Depth Cased 120 Feet
EXISTING CASING SCHEDULE
Table with columns: Size O.D. (Inches), Weight/Ft. (Pounds), Wall Thickness (Inches), From (Feet), To (Feet).
Row 1: 4", 80, 0, 0, 120

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? yes no
If well was not cleaned out to total depth, please explain why:
Was the well contaminated? yes no
Was the casing pulled? yes no
Was the casing over drilled? yes no

Existing Perforations:
Type of perforation FACTORY SLOT
Size of perforation 1.20
From 6.5 feet to 120 feet

Additional Perforations:
Type of perforator used:
From feet to feet Number of perfs per linear foot

5 WATER LEVEL
Static water level feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

8 WELL PLUGGING MATERIALS
Table with columns: From (feet), To (feet), Material Used, Pumped, Poured.
Row 1: 0, 120, NEAT CEMENT, Pumped, Poured

6 Additional Notes or Comments
MADE ATTEMPT TO PULL CASING WITH NO EFFECT
- RAN TRIMMER TO BOTTOM PUMPED NEAT CEMENT FROM BOTTOM UP.
PLUGGED AND ADDED 80 PSI PRESSURE FOR 15 MIN TO BE DROPPED OFF TO SURFACE
RECEIVED 2015 APR - 8 AM 10:25 STATE ENGINEERS OFFICE
NAD 27
40.882452°N
117.143876°W

Neat Cement Fluid Weight lbs/gal
Bentonite Grout % bentonite 6 gal
Date Started 1-22-15
Date Completed 1-22-15

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name CASCADE DRILLING Contractor
Address 230 E. STONEY DR Contractor
Mc CARRAN, NV
Nevada contractor's license number issued by the State Contractor's Board 73966
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2434
Signed [Signature] By driller performing actual drilling on-site or contractor
Date 1-22-15