STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 122126
Permit No.
Basin 071

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 72099

1. OWNER Julio Martinez
MAILING ADDRESS 3085 Middleway
WMCA NV 89445

ADDRESS AT WELL LOCATION Corner of Forest And N. Lorain Ct. WMCA NV
Subdivision Name: Brad Shell County: Humboldt

2. LOCATION NW ¼ NW ¼ Sec 7 T 35 N/S R 38 E
PERMIT/WAIVER No. 3508-07-101-009
Issued by Water Resources Parcel No.

Latitude
Longitude
UTM E 436696 ☒ NAD 27
N 4530635 ☐ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Topsoil - Sand		0	10	10
Gravel - Sand		10	30	20
Rock		30	60	30
gravel - Clay		60	80	20
Clay - Rock		80	100	20
Hard Rock		100	120	20
mixed Clay - Rock		120	160	60
Hard rock		160	184	20
NAD 27				
40.926291°N				
117.751849°W				

RECEIVED 2015 APR -8 AM 10:24 STATE ENGINEERS OFFICE

Date started: 3-17, 20 15
Date completed: 3-25, 20 15

7. Water Level
Static water level: 60 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: Cold °F
Quality: Good

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Rotary	35	UNK	2 Hrs.

9. WELL CONSTRUCTION
Depth Drilled 180 Feet Depth Cased 180 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
10 5/8 Inches	0 Feet	180 Feet
inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	71	180

Perforations:
Type of perforation Sawed
Size of perforation 3/8 x 3"
From 140 feet to 184 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☐ Concrete Grout 5 to 40 ☐ Pumped ☒ Poured
☐ ≥80% Bentonite Grout to ☐ Pumped ☐ Poured
Gravel Pack: ☒ Yes ☐ No 130 to 184 ☐ Pumped ☒ Poured
Type:
Bentonite Chips: ☒ Yes ☐ No 40 to 130 ☐ Pumped ☒ Poured
Type: 3/8 Chips

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name LBJ DRILLING & PUMP COMPANY, INC.
Contractor
Address P.O. BOX 902 - Winnemucca, NV 89446
Contractor

Nevada contractor's license number issued by the *State Contractor's Board* 0009605A
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1807

Signed Joe Boggio
By driller performing actual drilling on site or contractor Joe Boggio
Date

USE ADDITIONAL SHEETS IF NECESSARY