WELL ID
MW 06

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 122267
Permit No.
Basin

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 37451

1. OWNER Nevada Env. resp. trust
MAILING ADDRESS 35 E. Wacker DR 1550
Chicago IL 60601

ADDRESS AT WELL LOCATION 501 S Fourth st. Henderson Nevada
Subdivision Name: Blackmt. ind. complex County: Clark

2. LOCATION NW ¼ SE ¼ Sec 12 T 22 N/S R 62 E
PERMIT/WAIVER No. MO-3034 178-12-701-004
Issued by Water Resources Parcel No.

Latitude 36.0469503° N
Longitude -115.0021847° W
UTM E ☐ NAD 27
N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Hollow stem auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Loose Sand		0	5	5
Sandy Gravel		5	10	5
Sandy Gravel		10	15	5
Silty sand		15	20	5
Coarse sand		20	25	5
Sand, moist		25	30	5
Silty clay		30	32	2

DCNR/DWR/SNBD
RECEIVED
APR 07 2015

Date started: March 24, 20 15
Date completed: March 24, 20 15

9. WELL CONSTRUCTION
Depth Drilled 32 Feet Depth Cased 32 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
8	Inches	0	Feet	32	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2		Sch. 40	0	32

Perforations:
Type of perforation Slotted
Size of perforation .020
From 32 feet to 22 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☒ Cement Grout 18' to 3' ☐ Pumped ☒ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ☒ Yes ☐ No 32 to 21 ☐ Pumped ☒ Poured
Type: 2/12 sand
Bentonite Chips: ☒ Yes ☐ No 21' to 18' ☐ Pumped ☒ Poured
Type: Medium bentonite chips

7. Water Level
Static water level: 24 feet below land surface
Artesian Flow: N/A G.P.M. N/A P.S.I.
Water Temperature: N/A °F
Quality: N/A

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Luis Torres - Gregg Drilling
Contractor
Address 2726 Walnut AVE Signal Hill CA 90755
Contractor

Nevada contractor's license number issued by the State Contractor's Board 0038113
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2435-M

Signed [signature]
By driller performing actual drilling on-site or contractor
Date 3·26·15

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY

36.0469742
-115.001358
NAD 27

(NSPO 3-08) (O) 627