STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 122353
Permit No.
Basin No. 141

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 73468
WELL NAME *(If applicable)*:

1. OWNER/CLIENT NAME Numa Dorthy Dressauer
MAILING ADDRESS 870 S. Barlow lane, Bishop, CA 93514
DETAILED ADDRESS AT WELL LOCATION Belmont - Lot 1 Block 8
Subdivision Name: Belmont townsite County: NYE

2. PLS LOCATION SE ¼ NE ¼ 26 Sec 9 T 0 S 45 E
PERMIT/WAIVER NO. 004-533-01
Issued by Water Resources *Current Parcel No.*
Latitude 38° 35.794 UTM E ☐ NAD 27
Longitude 116° 52.508 UTM N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☒ Rotary ☐ RVC
☒ Air ☐ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To	Thickness
Alovial			0	5	5
Black schell		105	5	140	135
		130			
Nad 27					
38.596633					
116.872239					

Date started: 5-12, 20 15
Date completed: 5-12, 20 15

9. WELL CONSTRUCTION
Depth Drilled: 140 Feet Depth Cased: 140 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 5/8	Inches	0	Feet	140	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	8	.188	+18	140

PERFORATIONS:
Type of perforation: Mill Slot
Size of perforation: 3 By 3/16
From 120 Feet To 140 Feet
From Feet To Feet
From Feet To Feet

ANNULAR MATERIALS

☒ Sanitary Seal	0	to 100		
☒ Neat Cement	0	to 20	☐ Pumped	☒ Poured
☐ Cement Grout		to	☐ Pumped	☐ Poured
☐ Concrete Grout		to	☐ Pumped	☐ Poured
☒ Bentonite Chips	20	to 100	☐ Pumped	☒ Poured
☐ Bentonite Grout		to	☐ Pumped	☐ Poured
☐ 15 % ☐ 20 % ☐ Other, explain:				
☒ Gravel Pack [> 0.2 in.]	100	to 140	☐ Pumped	☒ Poured
☐ Sand Pack [< 0.2 in.]		to	☐ Pumped	☐ Poured
☐ Other, explain:		to	☐ Pumped	☐ Poured

7. WATER QUALITIES
Static water level: 36 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: 54 ° Fahrenheit
Water Quality:

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
+100		10

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name Rosenlund Drilling LLC *Contractor*
Address HC 60 Box 890 Ruby Valley NV 89833 *Contractor*
Nevada contractor's license number as issued by the *State Contractor's Board:* 0079932
Nevada well driller's license number as issued by the *Nevada Division of Water Resources (on-site driller):* 2465
Signed: Logan Rosenlund *By driller performing actual drilling on site or contractor*
Date: 5-13-14

USE ADDITIONAL SHEETS IF NECESSARY

(Rev. 08-12)
(NSPO Rev 11-12)
(O) 627