STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 122418
Permit No.
Basin No. 070

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 72645
WELL NAME *(if applicable)*:

1. OWNER/CLIENT NAME Finance All LLC
MAILING ADDRESS 20272 West Valley Blvd.
Tehachapi CA 93561

DETAILED ADDRESS AT WELL LOCATION Sierra Pass Rd.
Winnemucca NV
Subdivision Name: Blue Mtn Ranches *County:* Humboldt

2. PLS LOCATION NE ¼ SE ¼ 17 Sec 36 N/S 36 E
PERMIT/WAIVER NO. 36361/100009
Issued by Water Resources *Current Parcel No.*

Latitude N40*59.714 UTM E ☐ NAD 27
Longitude W117*56.882 UTM N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☒ Rotary ☐ RVC
☐ Air ☒ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
Sand		No	0	10
Sand Gravel Clay		No	10	160
Hard Grey and green clay with				
hard blck shale layers			160	360

NAD 27
40.995330°N
117.947063°W

Date started: 14-Apr , 20 15
Date completed: 05/01/15 , 20 15

7. WATER QUALITIES
Static water level: 85 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: 60 ° Fahrenheit
Water Quality: Clear

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
25	N/A	8

9. CONSTRUCTION
Depth Drilled: 360 Feet Depth Cased: 360 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 5/8"	Inches	0	Feet	360	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8"	steel	.188	0	20
6 5/8"	pvc	Sched 40	20	360

ANNULAR MATERIALS
Sanitary Seal X ☒ Yes ☐ No X

☒ Neat Cement	0	to	20	☐ Pumped	☒ X Poured
☐ Cement Grout		to		☐ Pumped	☐ Poured
☐ Concrete Grout		to		☐ Pumped	☐ Poured
☒ Bentonite Chips	20	to	50	☐ Pumped	☒ Poured
☒ Gravel Pack [> 0.2 in.]	50	to	360	☐ Pumped	☒ Poured
☐ Sand Pack [< 0.2 in.]		to		☐ Pumped	☐ Poured
☐ Other, explain:		to		☐ Pumped	☐ Poured

PERFORATIONS:
Type of perforation: slot
Size of perforation: 0.2

From 300	Feet	To 360	Feet
From	Feet	To	Feet
From	Feet	To	Feet
From	Feet	To	Feet
From	Feet	To	Feet

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name Allied Drilling Inc.
Contractor
Address 5140 Jungo Rd Winnemucca NV
Contractor
Nevada contractor's license number as issued by the *State Contractor's Board:* 76778
Nevada well driller's license number as issued by the *Nevada Division of Water Resources (on-site driller):* 5563
Signed:
By driller performing actual drilling on site or contractor
Date 5-6-15

RECEIVED 2015 MAY 11 AM 8:15 STATE ENGINEER'S OFFICE

(Rev. 12-13) USE ADDITIONAL SHEETS IF NECESSARY pg. of pg.