STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 122644
Permit No.
Basin No. 044

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 73146-2
WELL NAME *(If applicable)*: MO #3

1. OWNER/CLIENT NAME RYNDON ON TAHE RIVER LLC
MAILING ADDRESS 5677 ALPHA AVE
RENO, NV 89506

DETAILED ADDRESS AT WELL LOCATION 507 SCOTT RD
KOA CAMPGROUND
Subdivision Name: SPECIAL LANDS *County:* ELKO

2. PLS LOCATION NE ¼ SW ¼ 6 Sec 35N N/S 57 E
PERMIT/WAIVER NO. M/O 1999 *Issued by Water Resources* 006-54D-002 *Current Parcel No.*

Latitude
Longitude
UTM E 618095
UTM N 4533412
☒ NAD 27 ☐ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☒ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☒ Rotary ☐ RVC
☒ Air ☐ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
SAND			0	13
SAND & GRAVEL		X	13	24
THREADED PLUG ON BOTTOM OF CASING				
NAD27 40.945222°N 115.597023°W				

Date started: 10-Jun, 20 15
Date completed: 10-Jun, 20 15

9. CONSTRUCTION
Depth Drilled: 24 Feet Depth Cased: 22 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
6 1/8 Inches		0 Feet	24 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2	0.7	SCH 40 PVC	+1	22
6.625	13	.188	+1.5	5

ANNULAR MATERIALS
Sanitary Seal ☒ Yes ☐ No

☒ Neat Cement	0 to 8	☐ Pumped	☒ Poured
☐ Cement Grout	to	☐ Pumped	☐ Poured
☐ Concrete Grout	to	☐ Pumped	☐ Poured
☒ Bentonite Chips	8 to 10	☐ Pumped	☒ Poured
☐ Gravel Pack [> 0.2 in.]	to	☐ Pumped	☐ Poured
☒ Sand Pack [< 0.2 in.]	10 to 22	☐ Pumped	☒ Poured
☐ Other, explain:	to	☐ Pumped	☐ Poured

PERFORATIONS:
Type of perforation: FACTORY SCREEN
Size of perforation: 0.02
From 12 Feet To 22 Feet
From Feet To Feet
From Feet To Feet
From Feet To Feet
From Feet To Feet

7. WATER QUALITIES
Static water level: 12 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: 65 ° Fahrenheit
Water Quality: GOOD

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
1 1/2		1 HOUR

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name HACKWORTH DRILLING INC. Contractor
Address P.O. BOX 850, ELKO, NV 89803 Contractor
Nevada contractor's license number as issued by the *State Contractor's Board:* 020582
Nevada well driller's license number as issued by the *Nevada Division of Water Resources (on-site driller):* 1166
Signed: Dale C. Verden *By driller performing actual drilling on site or contractor*
Date: 6/12/2015

RECEIVED 2015 JUN 25 AM 11:58 STATE ENGINEER'S OFFICE

(Rev. 12-13) USE ADDITIONAL SHEETS IF NECESSARY pg. of pg.